

GPFC160-28

GPFC160-28 Information

	Part Number	GPFC160-28	
Heisener.com	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	
	Description	AC/DC CONVERTER 28V 160W	13446324
	Package	-	- FEI 1444
For Reference Only		For the pricing/inventory/lead time, please contact	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GPFC160-28 Specifications

Manufacturer SL Power Electronics Manufacture of Condor/Ault Brands Category Power Supplies - External/Internal (Off-Board) AC DC Converters AC DC Converters Package - Stries GPFC160 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 4 - Voltage - Solation IntE (Commercial) Power (Watts) IGOW Applications ITE (Commercial) Voltage - Isolation - Efficiency - Operating Temperature Of°C ~ 50°C Features Adjustable Output, PFC, Remote Sense, Universal Input Mounting Type	_			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GPFC160 Streps Open Frame Number of Outputs 1 Voltage - Input S5 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation FIE (Commercial) Voltage - Isolation -	Manufacturer Part Number	GPFC160-28		
AC DC Converters Package - Series GPFC160 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Soltput 4 - Voltage - Soltput 4 - Voltage - Soltput 4 - Voltage - Isolation - Voltage - Isolation - Efficiency - Operating Temperature O°C ~ So°C Features Adjustable Output, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.0°L x 4.50° W x 1.70° H (177.8mm x 114.	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGPFC160TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Power (Watts)160WApplicationsITE (Commercial)Voltage - Isolation-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChasis MountSiz / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series GFFC160 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 160W Applications ITE (Commercial) Voltage - Isolation - Operating Temperature 0°C ~ 50°C Features Adjustable Output PFC, Remote Sense, Universal Input Mounting Type Chasis Mount Size / Dimension 10°U 'L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)		AC DC Converters		
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation InfE (Commercial) Voltage - Isolation - Voltage - Isolation - <td< td=""><td>Package</td><td>-</td></td<>	Package	-		
Number of Outputs I Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solutput 4 - Voltage - Isolation - Voltage - Isolation - Efficiency - Voltage - Isolation - Efficiency - Operating Temperature 0°C ~ 50°C Features Adjustable Output, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8m x 114.3mm x 43.2mm)	Series	GPFC160		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Watts) 160W Applications ITE (Commercial) Voltage - Isolation - Voltage - Isolation - Operating Temperature 0°C ~ 50°C Features Adjustable Output, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Туре	Open Frame		
Voltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5APower (Watts)160WApplicationsITE (Commercial)Voltage - Isolation-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting Type7.00°L x 4.50°W x 1.70°H (177.8mm x 114.3mm x 43.2mm)	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5APower (Watts)160WApplicationsITE (Commercial)Voltage - Isolation-Efficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting Type7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5APower (Watts)160WApplicationsITE (Commercial)Voltage - Isolation-Efficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 1	28V		
Voltage - Output 4-Current - Output (Max)5APower (Watts)160WApplications17E (Commercial)Voltage - Isolation-Fficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 2	-		
Current - Output (Max)5APower (Watts)160WApplicationsITE (Commercial)Voltage - Isolation-Efficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 3	-		
Power (Watts)160WApplicationsITE (Commercial)Voltage - Isolation-Efficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation-Efficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Current - Output (Max)	5A		
Voltage - Isolation-Efficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Power (Watts)	160W		
Efficiency-Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Applications	ITE (Commercial)		
Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, PFC, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Efficiency	-		
Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Operating Temperature	0° C ~ 50° C		
Size / Dimension 7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)	Features	Adjustable Output, PFC, Remote Sense, Universal Input		
	Mounting Type	Chassis Mount		
Report error	Size / Dimension	7.00" L x 4.50" W x 1.70" H (177.8mm x 114.3mm x 43.2mm)		
L		Report errors?		

GPFC160-28 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GPFC160-28 Payment Methods Image: WIRE transfer PayPai Image: Construction of the better GPFC160-28 Shipping Methods Image: Construction of the better GPFC160-28 Shipping Methods Image: Construction of the better Image: Construction of the better

If you have any question about GPFC160-28, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com