

GPM130A

GPM130A Information

	Part Number	GPM130A	
Contraction of the second seco	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	0.380
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	- 536 - 8
	Description	AC/DC CNVRTR 5V +/-12V 12V 100W	- 16 G.C.
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GPM130A Specifications

ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesGPM130SpriesGPM130Voltage of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 412VVoltage - Output 410W (130W Forced Air)ApplicationsTE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating TemperatureGlyatable Output, Remote Sense, Universal InputMounting TypeChasis Mount	-			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GPM130 Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 5 -12V Voltage - Output 6 -12V Voltage - Output 7 16A, 5A, 1.2A, 1.2A Power (Watts) 100W (130W Forced Air) Applications - Efficiency 70% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 50° L x 4.50° W x 2.00° H (215.9mm x 114.3mm x 50.8mm)	Manufacturer Part Number	GPM130A		
AC DC ConvertersPackage-SeriesGPM130TypeOpen FrameNumber of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 412VCurrent - Output (Max)16A, 5A, 1.2A, 1.2APower (Watts)100W (130W Forced Air)Applications-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeStor L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGPM130TypeOpen FrameNumber of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 412VVoltage - Output 412VVoltage - Output 410W (130W Forced Air)Current - Output (Max)ITE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating TemperatureO'C ~ 50°CFeaturesAdjustable Output 4.200" H (215.9mm x 114.3mm x 50.8mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series GPM130 Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 16A, 5A, 1.2A, 1.2A Power (Watts) 100W (130W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 0% Operating Temperature 0%C ~ 50°C Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension \$50°' L x 4.50'' W x 2.00'' H (215.9mm x 114.3mm x 50.8mm)		AC DC Converters		
Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 4 12V Voltage - Output 4 12V Voltage - Output 4 10W (130W Forced Air) Power (Watts) 10W (130W Forced Air) Applications - Voltage - Isolation - Efficiency 70% Operating Temperature Oic ~ 50°C Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chasis Mount Size / Dimension Size '' L x 4.50''' W x 2.00''' H (215.9mm x 114.3mm x 50.8mm)	Package	-		
Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 16A, 5A, 1.2A, 1.2A Power (Watts) 100W (130W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 8.50° L x 4.50° W x 2.00° H (215.9mm x 114.3mm x 50.8mm)	Series	GPM130		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Voltage - Output 4 12V Current - Output (Max) 16A, 5A, 1.2A, 1.2A Power (Watts) 100W (130W Forced Air) Applications TTE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Туре	Open Frame		
Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 12V Current - Output (Max) 16A, 5A, 1.2A, 1.2A Power (Watts) 100W (130W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Number of Outputs	4		
Voltage - Output 212VVoltage - Output 3-12VVoltage - Output 412VCurrent - Output (Max)16A, 5A, 1.2A, 1.2APower (Watts)100W (130W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-12VVoltage - Output 412VCurrent - Output (Max)16A, 5A, 1.2A, 1.2APower (Watts)100W (130W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Voltage - Output 1	5V		
Voltage - Output 412VCurrent - Output (Max)16A, 5A, 1.2A, 1.2APower (Watts)100W (130W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Voltage - Output 2	12V		
Current - Output (Max)16A, 5A, 1.2A, 1.2APower (Watts)100W (130W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Voltage - Output 3	-12V		
Power (Watts)100W (130W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Voltage - Output 4	12V		
ApplicationsITE (Commercial), MedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Current - Output (Max)	16A, 5A, 1.2A, 1.2A		
Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Power (Watts)	100W (130W Forced Air)		
Efficiency70%Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Applications	ITE (Commercial), Medical		
Operating Temperature0°C ~ 50°CFeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Efficiency	70%		
Mounting Type Chassis Mount Size / Dimension 8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Operating Temperature	0° C ~ 50° C		
Size / Dimension 8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)	Features	Adjustable Output, Remote Sense, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	8.50" L x 4.50" W x 2.00" H (215.9mm x 114.3mm x 50.8mm)		
		Report errors ⁶		

GPM130A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

GPM130A Payment Methods WIRE transfer PayPal Methods GPM130A Shipping Methods



If you have any question about GPM130A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com