

# GPM225-12

#### **GPM225-12 Information**

	Part Number	GPM225-12	
Heisener.com	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	回訳法回
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	
	Description	AC/DC CONVERTER 12V 175W	
	Package	-	「同社会社」
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GPM225-12 Specifications**

ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsPackage>AC DC ConvertersPackage>SeriesGPM225TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Power (Watts)-Voltage - Soltation-Voltage - Soltation-Voltage - Soltation-Porter Soltation-Voltage - Soltation-Voltage - Soltation-Voltage - Soltation-Voltage - Soltation-Porter Soltation-Porter Soltation-Voltage - Soltation-Voltage - Soltation-Voltage - Soltation-Voltage - Soltation-Voltage - Solt	-			
Category Power Supplies - External/Internal (Off-Board)   AC DC Converters   Package -   Series GPM225   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 12V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Solation 15W (225W Forced Air)   Power (Watts) -   Applications Medical   Voltage - Isolation -   Voltage - Isolation -   Efficiency 0%   Operating Temperature 0%C ~ 50°C (With Derating)   Features Adjustable Output, Remote Sense, Universal Input   Mounting Type	Manufacturer Part Number	GPM225-12		
AC DC ConvertersPackage-SeriesGPM225TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)16APower (Watts)175W (225W Forced Air)Voltage - Isolation-Voltage - Solation-Voltage - Solation-Kedical-Current - Output for Max)-ApplicationsMedicalVoltage - Solation-Chrester Max-Sterler Solation-Chasis Mount-FeaturesAdjustable Output, Remote Sense, Universal InputMounting Type-Size / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGPM225TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 416APower (Wats)15W (225W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency0°C ~ 50°C (With Derating)PeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeSies MountSize / Dimension9.0° L x 5.00° W x 2.50° H (228.6mm x 127.0mm x 63.5mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series GPM225   Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 12V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 16A   Power (Watts) 175W (225W Forced Air)   Applications Medical   Voltage - Isolation -   Efficiency 70%   Operating Temperature Adjustable Output, Remote Sense, Universal Input   Mounting Type Chassis Mount   Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)		AC DC Converters		
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 46Current - Output (Max)16APower (Watts)NedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting Type9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Package	-		
Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 12V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 16A   Power (Watts) 175W (225W Forced Air)   Applications Medical   Voltage - Isolation -   Efficiency 70%   Operating Temperature 0°C ~ 50°C (With Derating)   Features Adjustable Output, Remote Sense, Universal Input   Mounting Type Chassis Mount   Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Series	GPM225		
Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 12V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 16A   Power (Watts) 175W (225W Forced Air)   Applications Medical   Voltage - Isolation -   Efficiency 70%   Operating Temperature 0°C ~ 50°C (With Derating)   Features Adjustable Output, Remote Sense, Universal Input   Mounting Type Chassis Mount   Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Туре	Open Frame		
Voltage - Output 1 12V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 16A   Power (Watts) 175W (225W Forced Air)   Applications Medical   Voltage - Isolation -   Efficiency 0°C ~ 50°C (With Derating)   Operating Temperature Adjustable Output, Remote Sense, Universal Input   Mounting Type Chassis Mount   Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)16APower (Watts)175W (225W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting Type9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)16APower (Watts)175W (225W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting Type9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Output 1	12V		
Voltage - Output 4-Current - Output (Max)16APower (Watts)175W (225W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting Type9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Output 2	-		
Current - Output (Max)16APower (Watts)175W (225W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)PeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Output 3	-		
Power (Watts)175W (225W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Output 4	-		
ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)PeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Current - Output (Max)	16A		
InInVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Power (Watts)	175W (225W Forced Air)		
Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Applications	Medical		
Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Efficiency	70%		
Mounting TypeChassis MountSize / Dimension9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Operating Temperature	$0^{\circ}$ C ~ $50^{\circ}$ C (With Derating)		
Size / Dimension 9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)	Features	Adjustable Output, Remote Sense, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	9.00" L x 5.00" W x 2.50" H (228.6mm x 127.0mm x 63.5mm)		
		Report errors?		

#### **GPM225-12 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about GPM225-12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com