

GPM55-24

GPM55-24 Information

	Part Number	GPM55-24	
Contense and the second	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	242
	Description	AC/DC CONVERTER 24V 55W	- <u>1966</u>
	Package	-	i i î î î î î î î î î î î î î î î î î î
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GPM55-24 Specifications

ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesGPM55StresGPM55Voltage Outputs1Voltage - Output 155 ~ 264 VACVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 1-Voltage - Output 1-Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7-Voltage - Output 9-Voltage - Output 9-Voltage - Output 9-Voltage - Output 9-Voltage - Soltaion-Power (Watts)-Voltage - Isolation-Pore - Soltaion-Pore - Soltaion-Pore - Soltaion-Pore - Soltaion-Pore - Soltaion-FeaturesAdjustable Output, Universal InputFeaturesMounting TypeMounting TypeChasis Mount	-			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GPM55 Stries GPM55 Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 6 - Voltage - Output 7 - Voltage - Output 8 - Voltage - Output 9 - Voltage - Output 4 - Current - Output (Max) 2.3A Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Universal Input Fouring Type Chassis Mount Size / Dimension 6.30° L x 3.94° W x 1.68° H (160.0mm x 100.0mm x 42.7mm)	Manufacturer Part Number	GPM55-24		
AC DC Converters Package - Series GPM55 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.3A Power (Watts) 55W Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.30° L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGPM55TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 455WApplicationsMedicalVoltage - Isolation-Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeGasis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series GPM55 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.3A Power (Watts) 55W Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.30° L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)		AC DC Converters		
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solution 4 - Voltage - Isolation - Voltage -	Package	-		
Number of Outputs I Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.3A Power (Watts) 55W Applications Medical Voltage - Isolation - Efficiency 0% C ~ 50°C (With Derating) Operating Temperature 0°C ~ 50°C (With Derating) Mounting Type Chassis Mount Size / Dimension 6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Series	GPM55		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.3A Power (Watts) 55W Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.30° L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Туре	Open Frame		
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.3A Power (Watts) 55W Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature O°C ~ 50°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.3APower (Watts)55WApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.3APower (Watts)55WApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Voltage - Output 1	24V		
Voltage - Output 4-Current - Output (Max)2.3APower (Watts)55WApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 42.7mm)	Voltage - Output 2	-		
Current - Output (Max)2.3APower (Watts)55WApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)PeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 42.7mm)	Voltage - Output 3	-		
Power (Watts)55WApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 42.7mm)	Voltage - Output 4	-		
ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 42.7mm)	Current - Output (Max)	2.3A		
Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Power (Watts)	55W		
Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Applications	Medical		
Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Efficiency	70%		
Mounting TypeChassis MountSize / Dimension6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Operating Temperature	0° C ~ 50° C (With Derating)		
Size / Dimension 6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)	Features	Adjustable Output, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	6.30" L x 3.94" W x 1.68" H (160.0mm x 100.0mm x 42.7mm)		
1		I	Report errors?	

GPM55-24 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GPM55-24 Payment Methods Image: Ima

If you have any question about GPM55-24, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com