

GPM80-28

GPM80-28 Information

	Part Number	GPM80-28	
Contraction of the second seco	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	IN AN I
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	
	Description	AC/DC CONVERTER 28V 80W	2 <u>22</u> 2
	Package	-	i i i state i
For Reference Only		For the pricing/inventory/lead time, please contact	ERU/1980
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GPM80-28 Specifications

Manufacturer Part NumberGPM80-28ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesGPM80TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)29APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency0%Operating Temperature0%C ~ 50°C (With Derating)	-			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series GPM80 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 85 ~ 264 VAC Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Soltput 4 - Voltage - Soltput 4 - Voltage - Soltput 5 Secold Air) Applications - Voltage - Isolation - Fifticiency Ot% Cov°C (With Derating)	Manufacturer Part Number	GPM80-28		
AC DC ConvertersPackage-SeriesGPM80TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4SowOpen FrameSowVoltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 4-Current - Output (Max)2.9APower (Watts)MedicalVoltage - Isolation-Voltage - Isolation-Fificiency70%Operating Temperature0°C ~ 50°C (With Derating)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGPM80TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 49.9AVoltage - Output 40.9APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Voltage - Isolation0%Operating Temperature0°C ~ 50°C (With Derating)	Category	Power Supplies - External/Internal (Off-Board)		
SeriesGPM80TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4.9APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Friciency70%Operating Temperature0°C ~ 50°C (With Derating)		AC DC Converters		
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4SW(110W Forced Air)Power (Watts)MedicalApplications-Voltage - Isolation-Ffficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Package	-		
Number of Outputs I Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 2.9A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating)	Series	GPM80		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.9A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating)	Туре	Open Frame		
Voltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.9APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.9APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.9APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Voltage - Output 1	28V		
Voltage - Output 4-Current - Output (Max)2.9APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Voltage - Output 2	-		
Current - Output (Max)2.9APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Voltage - Output 3	-		
Power (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Voltage - Output 4	-		
ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Current - Output (Max)	2.9A		
Image: Notation-Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Power (Watts)	80W (110W Forced Air)		
Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)	Applications	Medical		
Operating Temperature $0^{\circ}C \sim 50^{\circ}C$ (With Derating)	Voltage - Isolation	-		
	Efficiency	70%		
Features Adjustable Output Remote Sense Universal Input	Operating Temperature	0° C ~ 50° C (With Derating)		
regustuole output, remote bense, om rorsul input	Features	Adjustable Output, Remote Sense, Universal Input		
Mounting Type Chassis Mount	Mounting Type	Chassis Mount		
Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Size / Dimension	7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)		
Report errors?		Report errors?		

GPM80-28 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GPM80-28 Payment Methods Image: WIRE transfer PayPal Image: Construction of the better GPM80-28 Shipping Methods Image: Construction of the better GPM80-28 Shipping Methods Image: Construction of the better GPM80-28 Shipping Methods Image: Construction of the better Image: Construction of the better Image: Construction of the better

If you have any question about GPM80-28, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com