

GPS-310FS

GPS-310FS Information

	Part Number	GPS-310FS
Rom	Manufacturer	RF Solutions
ALL SAN	Category	RF/IF and RFID RF Receivers
	Description	GPS MODULE SMD 16CH
	Package	Module
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GPS-310FS Specifications

Manufacturer Part Number GPS-310FS Manufacturer RF Solutions Category RF/IF and RFID Category RF Receivers Package Module Series - Frequency 1575.42MHz Sensitivity -155dBm Data Rate (Max) - Modulation or Protocol GPS Receivers Qurrent - Receiving GPS Receivers Memory Size - Antenna Connector PCB, Surface Mount Features - Voltage - Supply 3V ~ 3.6 V Operating Temperature -40°C ~ 85°C Package / Case Module		
CategoryRF/F and RFIDRF ReceiversPackageModulePackageModuleSeries-Frequency1575.42MHzSensitivity-155dBmData Rate (Max)-Modulation or ProtocolGPSApplicationsGPS ReceiversCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures3 V ~ 3.6 VOttage - Supply-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Manufacturer Part Number	GPS-310FS
Indext stateRF ReceiversPackageModuleSeries-Frequency1575.42MHzSensitivity-Data Rate (Max)-Modulation or ProtocolGPSApplicationsGPS ReceiversCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures3V ~ 3.6 VOtage - Supply-Operating Temperature40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Manufacturer	RF Solutions
PackageModuleSeries-Frequency157542MHzSensitivity-155dBmData Rate (Max)-Modulation or ProtocolGPSApplicationsGPS ReceiverCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3V ~ 3.6 VOperating Temperature40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Category	RF/IF and RFID
Series - Series - Frequency 1575.42MHz Sensitivity -155dBm Data Rate (Max) - Modulation or Protocol GPS Applications GPS Receiver Current - Receiving 45mA Data Interface Pads for Pins Memory Size - Antenna Connector PCB, Surface Mount Features - Voltage - Supply 3 V ~ 3.6 V Operating Temperature 40°C ~ 85°C Package / Case Module Supplier Device Package Module		RF Receivers
Frequency1575.42MHzSensitivity-155dBmData Rate (Max)-Modulation or ProtocolGPSApplicationsGPS ReceiverCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Package	Module
Sensitivity-155dBmData Rate (Max)-Modulation or ProtocolGPSApplicationsGPS ReceiverCurrent - Receiving45mAData InterfacePads for PrinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-Package / CaseModuleSupplier Device PackageModule	Series	-
Data Rate (Max)-Modulation or ProtocolGPSApplicationsGPS ReceiverCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Frequency	1575.42MHz
Modulation or ProtocolGPSApplicationsGPS ReceiverCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Sensitivity	-155dBm
ApplicationsGPS ReceiverCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Data Rate (Max)	-
InCurrent - Receiving45mAData InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Modulation or Protocol	GPS
Data InterfacePads for PinsMemory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Applications	GPS Receiver
Memory Size-Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Current - Receiving	45mA
Antenna ConnectorPCB, Surface MountFeatures-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Data Interface	Pads for Pins
Features-Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Memory Size	-
Voltage - Supply3 V ~ 3.6 VOperating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Antenna Connector	PCB, Surface Mount
Operating Temperature-40°C ~ 85°CPackage / CaseModuleSupplier Device PackageModule	Features	-
Package / CaseModuleSupplier Device PackageModule	Voltage - Supply	3 V ~ 3.6 V
Supplier Device Package Module	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module
Report errors?	Supplier Device Package	Module
		Report errors?

GPS-310FS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GPS-310FS Payment Methods Image: WiRE transfer PayPai Image: Consequence of the tester Image: Consequence of tes

If you have any question about GPS-310FS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com