

GSA32DTBT

uest a Quote

GSA32DTBT Information

Heisener.com	Part Number	GSA32DTBT	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 64POS 0.125	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GSA32DTBT Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row32Number of Positions0.602" (1.57mm)Number of Rows2Pitch0.1025" (3.18mm)Features-Mounting TypeSolderContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIopin BionszeContact TypeIopin BionszeContact TypeSolderContact Finish ThicknessJouin (0.25µm)Contact TypeIopie BionszeContact TypeIopie BionszeContact TypeIopie BionszeColare TypeIopie BionszeColare TypeIopie BionszeColare TypeBickFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row32Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness0.062Contact TypeInjun (0.25µm)Contact TypeLoop BellowsContact TypeSolderContact TypeInjun (0.25µm)Contact TypeInjun (0.25µm)Contact TypeSolderContact TypeInjun (0.25µm)Contact TypeInjun (0.25µm)Contact TypeSolderCoperating FeatureFlush Mount, Top Opening, Threaded Insert, 440Operating Temperature-5°C ~ 125°C	Manufacturer Part Number	GSA32DTBT	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row32Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact Material9olderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange Feature-S°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row32Number of Positions64Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialGoldContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange Feature-S°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row32Number of Positions64Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row32Number of Positions64Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact TypeIopin BionzeContact TypeLoop BellowsColarBlackFange FeatureFush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row32Number of Positions64Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeLoop BellowsColorBlackFlange Feature-S0°C ~ 125°C	Series	-	
Number of Positions/Bay/Row32Number of Positions64Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeIop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 64 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Gold Contact Finish Gold Contact Type Loop Bellows Color Black Flange Feature Flush Mount, Top Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	32	
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	64	
Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Openating Temperatures-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.125" (3.18mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeLoop BellowsColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Threaded Insert, 4-40	
Report errors?	Operating Temperature	$-65^{\circ}\mathrm{C} \sim 125^{\circ}\mathrm{C}$	
			Report errors?

GSA32DTBT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GSA32DTBT Payment Methods





If you have any question about GSA32DTBT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com