

# **GSC10DRXH**

### **GSC10DRXH** Information

Heisener.com	 GSC10DRXH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 20POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GSC10DRXH Specifications**

Manufacturer Part Number GSC10DRXH   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors   Package -   Stries -   Gard Type Mon Specified - Dual Edge   Gender Kenale   Number of Positions/Bay/Row 10   Number of Positions/Bay/Row 0   Number of Positions 20   Strik 0.062° (1.57mm)   Number of Rows 2   Pactures .   Mounting Type .   Young Hole .   Young Hole .   Contact Material Solder   Contact Finish Thickness Gold   Contact Finish Thickness Iopin Orzen   Contact Finish Thickness Iopin Orzen   Contact Type Back   Color Back   Color Back   Color Back		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Nouning TypeMinogi HoleContact FinishSolderContact FinishGoldContact Finish Thickness10µín (0.5µm)Contact Finish Thickness10µín (0.5µm)ColarBlackFinage FeatureTop Mount Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature65° C + 125°C	Manufacturer Part Number	GSC10DRXH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Card Thickness0602" (1.57mm)Card Thickness0.602" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type10Contact MaterialSolderContact FinishGoldContact FinishGoldContact Finish Thickness10µi (0.25µm)Contact TypeHalellowsContact SpecifiesGoldContact Finish Thickness10µi (0.25µm)Colar TypeHalellowsContact Finish Thickness10µi (0.25µm)Colar TypeSolderColar TypeSolder </td <td>Manufacturer</td> <td>Sullins Connector Solutions</td>	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions/Bay/Row20Card Thickness0.662" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeNongh HoleContact MaterialSolderContact Finish Thickness0.602Contact Finish ThicknessGuldContact TypeHullellowsContact SeriesSolderContact Finish Thickness10µin (0.25µm)Contact Finish ThicknessBlackFolage FeatureTom Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenting Temperature65° ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessFeaturesContact Finish ThicknessFeaturesContact Finish ThicknessFeaturesContact Finish ThicknessFeaturesContact Finish ThicknessFeaturesColorBlackFinage Feature-for Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeMologe HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIpin (0.25µm)Contact TypeHole SolderContact Finish ThicknessSolderContact Finish ThicknessSolderColorBlackFange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-55°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Series	-
Number of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessInjin (0.25µm)Contact TypeHul BellowsColorBackFlange Feature-Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 20   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type -   Mounting Type Through Hole   Contact Material Solder   Contact Finish Gold   Contact Finish Thickness Ioµin (0.25µm)   Contact Type Full Bellows   Color Black   Flange Feature -   Operating Temperature -	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFul BellowsColorBackFlange FeatureCopy Contact Solution (0.125" (3.18mm) DiaOperating Temperature-	Number of Positions/Bay/Row	10
Number of Rows2Number of Rows0.100" (2.54mm)Features-Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange Feature-50°C ~ 125°C	Number of Positions	20
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

### **GSC10DRXH** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **GSC10DRXH** Payment Methods



### **GSC10DRXH Shipping Methods**



If you have any question about GSC10DRXH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com