

# GSC43DRTI-S93

est a Quote

### **GSC43DRTI-S93 Information**

Part Number	GSC43DRTI-S93
Manufacturer	Sullins Connector Solutions
Category Description Package	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
	CONN EDGE DUAL FMALE 86POS 0.100
	-
	For the pricing/inventory/lead time, please contact
For Reference Only	us
	Website: https://www.heisener.com E-mail: salesdept@heisener.com
	Manufacturer Category Description

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **GSC43DRTI-S93 Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIopin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsContact TypeSolderContact TypeSolder <tr< th=""><th></th><th></th></tr<>		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions/Bay/Row86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSolderContact TypeSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSolderContact TypeSolder </td <td>Manufacturer Part Number</td> <td>GSC43DRTI-S93</td>	Manufacturer Part Number	GSC43DRTI-S93
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeSolderContact Type50 Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions/Bay/Row86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeFeal HellowsContact TypeGoldContact TypeFull BellowsColorBlackFlange Feature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange Feature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeFull BellowsColorBiackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row43Number of Positions86Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange Feature-Operating Temperature-Solor C 125°C-	Card Type	Non Specified - Dual Edge
Number of Positions 86   Card Thickness 0.093" (2.36mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type -   Mounting Type Through Hole   Contact Material Solder   Contact Finish Gold   Contact Finish Thickness Iupin (0.25µm)   Contact Type Full Bellows   Color Black   Flange Feature Top Mount Opening, Threaded Insert, 4-40   Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBlackFlange Feature-50°C ~ 125°C	Number of Positions/Bay/Row	43
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange Feature-50°C ~ 125°C	Number of Positions	86
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.093" (2.36mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **GSC43DRTI-S93** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **GSC43DRTI-S93** Payment Methods



### **GSC43DRTI-S93** Shipping Methods



If you have any question about GSC43DRTI-S93, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com