

# **GSM18DRXS**

est a Quote

### **GSM18DRXS** Information

Heisener.com Gittal Write Land Terr	Part Number	GSM18DRXS	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 36POS 0.156	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GSM18DRXS** Specifications

Manufacturer Part Number GSM18DRXS   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors   Package -   Series -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 18   Number of Positions/Bay/Row 36   Number of Positions 36   Gard Thickness 0.062° (1.57mm)   Number of Rows 2   Pitch 0.156° (3.96mm)   Number of Rows 2   Features -   Mounting Type Piosph Fonze   Oract Material Solder   Contact Material Gold   Contact Finish Thickness Gold   Contact Finish Thickness Iopin O25µm)   Contact Type Black   Contact Type Black   Contact Type SideMoutOpening, Unthreaded, 0.125°, 0.318mm) Dia   Coperating Temperature SideMoutOpening, U	_		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Picth0.156" (3.96mm)Features-Nonging TypeSolderContact FinishSolderContact FinishGoldContact Finish ThicknessJujin (0.25µm)Contact Finish ThicknessSilellowsColorBackFaugre FeatureSideMoutOpening, Unthreaded, 0.125" (3.18mm) DiaColorSideMoutOpening, Unthreaded, 0.125" (3.18mm) DiaColorSideMoutOpening, Unthreaded, 0.125" (3.18mm) DiaColorating TypeSideMoutOpening, Unthreaded, 0.125" (3.18mm) DiaColorSideMoutOpening, Unthreaded, 0.125" (3.18mm) DiaColorSide	Manufacturer Part Number	GSM18DRXS	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Card Thickness0602" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type50derContact MaterialSolderContact FinishGoldContact FinishGoldContact Finish Thickness19uin (0.25µm)Colta TypeHalellowsColtar TypeSolderContact Finish Thickness60idColtar SeriesSolderColtar TypeSolderColtar TypeSolderColtar Finish ThicknessGoldColtar TypeSolderColtar TypeSolder	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeFolderContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBackFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenting Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness0.0d2Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBackFange Feature.50°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeBlackColorBlackFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating TemperatureSide ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type0.156" (3.96mm)TerminationSolderContact Material9hosphor BronzeContact Finish Thickness0.0dContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-Mounting TypeSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness0.161 (0.52µm)Contact TypeHul BellowsColorBackFlange FeatureSider Austral, 0.125" (3.18mm) DiaOperating Temperature-Solor Cards ColorSider Austral, 0.125" (3.18mm) DiaContact FinishSider Austral, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge	
Number of Positions 36   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole   Contact Material Solder   Contact Finish Gold   Contact Finish Thickness 10µin (0.25µm)   Contact Type Full Bellows   Color Black   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Number of Positions/Bay/Row	18	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	36	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFill BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)	
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$	
		Report errors?	

#### **GSM18DRXS** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **GSM18DRXS** Payment Methods



### **GSM18DRXS** Shipping Methods



If you have any question about GSM18DRXS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com