

GSM18DSEF-S243

GSM18DSEF-S243 Information

Heisener.com	 GSM18DSEF-S243 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 36POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GSM18DSEF-S243 Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Features-Nouting Type9.156" (3.96mm)FeaturesSolder EdgelsonNonting TypeSolder EdgelsonContact MaterialSolder EdgelsonContact FinishGoldContact Finish Thickness0.016" (3.96mm)Contact Finish ThicknessSolder EdgelsonContact Finish ThicknessSolder EdgelsonContact Finish ThicknessSolder EdgelsonContact Finish ThicknessSolder SciellowsColorBackFinage FeatureTo Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mouting Type9Poshor EductionSolder EductionFornitationSolder EductionContact FinishGoldContact Finish Thickness1041 (0.52mm)Contar Finish Thickness1041 (0.52mm)Contar Finish Thickness1041 (0.52mm)Colar EductionFinish (0.52mm)Colar EductionFinish (0.52mm)Finish Finish Thickness1041 (0.52mm)Colar EductionFinish (0.52mm)Finish Finish (0.52mm)Finish (0.	Manufacturer Part Number	GSM18DSEF-S243	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)ColorBlackFinage FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)ColorBlackFange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBackFinage FeaturesTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountPonet MaterialSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish ThicknessIujin (0.25µm)Contact TypeBale MountFolage FeatureFul BellowsFolage FeatureFul Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Package	-	
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBalckFlange FeaturesTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Series	-	
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFul BellowsContact TypeSolder Specific Spe	Card Type	Non Specified - Dual Edge	
Number of Positions36Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFil BellowsContact TypeSolder Solder Sol	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFul BellowsColorBackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Positions/Bay/Row	18	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFul BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Positions	36	
Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJuµin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Guenand Babbin, 0.116" (2.95mm) Dia	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Number of Rows	2	
Nounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Pitch	0.156" (3.96mm)	
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Mounting Type	Panel Mount	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Termination	Solder Eyelet(s)	
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish	Gold	
Color Black Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	Contact Type	Full Bellows	
	Color	Black	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia	
	Operating Temperature	-65°C ~ 125°C	
Report errors			Report errors?

GSM18DSEF-S243 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GSM18DSEF-S243 Payment Methods





If you have any question about GSM18DSEF-S243, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com