



GSM24DRXS Information

Heisener.com

Part Number GSM24DRXS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 48POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GSM24DRXS Specifications

Manufacturer Part Number Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Mounting Type Through Hole Termination Solder Contact Material Contact Finish Contact Finish Thickness Olio 10 Duin (0.25µm) Flangs Feature Side Mount Opening Inthreaded (0.125" (3.18mm) Dia	•	
Category Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color	Manufacturer Part Number	GSM24DRXS
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Black	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Black	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Black		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Package	-
Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Black	Series	-
Number of Positions/Bay/Row Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Black	Card Type	Non Specified - Dual Edge
Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Black	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Number of Positions/Bay/Row	24
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Number of Positions	48
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Card Thickness	0.062" (1.57mm)
Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Black	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Black	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlack	Contact Material	Phosphor Bronze
Contact Type Full Bellows Color Black	Contact Finish	Gold
Color Black	Contact Finish Thickness	10μin (0.25μm)
	Contact Type	Full Bellows
Flange Feature Side Mount Opening Unthreaded 0.125" (3.18mm) Dia	Color	Black
Fig. 1 catale Side Would Opening, Onlineaded, 0.125 (5.10iiiii) Dia	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-65°C ~ 125°C
Report error		Report errors?

GSM24DRXS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GSM24DRXS Payment Methods





















GSM24DRXS Shipping Methods













If you have any question about GSM24DRXS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com