

# **GSM24DSEH**

### **GSM24DSEH Information**

Heisener.com	Part Number Manufacturer Category Description Package	GSM24DSEH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 48POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GSM24DSEH Specifications**

Manufacturer Part Number GSM24DSEH   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors   Package -   Stries -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 24   Number of Positions/Bay/Row 48   Card Thickness 0.062° (1.57mm)   Number of Rows 2   Pich 0.156° (3.96mm)   Number of Rows 2   Pich 0.56° (3.96mm)   Features -   Mounting Type Piosphor Bronze   Contact Material Solder Eyelet(s)   Contact Finish Thickness Gold   Contact Finish Thickness Iopin O25µm)   Contact Finish Thickness Iopin O25µm)   Contact Type Back   Contact Type Back   Contact Type Back   Contact Type Solder Syncur <t< th=""><th></th><th></th></t<>		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions84Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Nounting TypePanel MountContact FinishSolder Eyels(s)Contact FinishGoldContact Finish Thickness10µín (0.25µm)Contact TypeFull BellowsColorBackFauge FeatureTop Mount Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature65° ~ 125°C	Manufacturer Part Number	GSM24DSEH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type9ale MountContact FinishSolder Eyele(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Coltact TypeHalellowsContact Finish Thickness6oldContact Finish Thickness10µin (0.25µm)Coltact TypeHalellowsColtact TypeGoldColtact TypeGold Solder So	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Card Thickness0.602" (1.57mn)Card Thickness0.602" (1.57mn)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish ThicknessIpin (0.25µm)Contact TypeFull BellowsColorBackFlange Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeFeallenssContact TypeFeallenssContact TypeSolder SympolensContact TypeFeallenssContact TypeFeallenssColorBlackFinage Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeBackColorBackFange Feature-55°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBackFlange Feature-Operating Temperature-Operating Temperature-<	Series	-
Number of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type9Ponter MaterialSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness0.96/l (0.25µm)Contact TypeHull BellowsColorBackFange Feature-Pinge Feature-Operating Temperature-Solder Color-Solder Schler S	Card Type	Non Specified - Dual Edge
Number of Positions 48   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Panel Mount   Termination Solder Eyelet(s)   Contact Material Posphor Bronze   Contact Finish Gold   Contact Type Full Bellows   Color Black   Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBackFlange FeatureCopy Contact Sing Type Contact Sing Con	Number of Positions/Bay/Row	24
Number of Rows2Nitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	48
Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFul BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypePanel MountHountSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI0µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Panel Mount
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder Eyelet(s)
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **GSM24DSEH Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **GSM24DSEH** Payment Methods



### **GSM24DSEH Shipping Methods**



If you have any question about GSM24DSEH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com