



## **GSM40DRMT-S288 Information**

Heisener.com

Part Number GSM40DRMT-S288

Manufacturer Sullins Connector Solutions Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

CONN EDGE DUAL FMALE 80POS 0.156 **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **GSM40DRMT-S288 Specifications**

	Report errors?
Operating Temperature	-65°C ~ 125°C
Flange Feature	Flush Mount, Top Opening, Threaded Insert, 4-40
Color	Black
Contact Type	Loop Bellows
Contact Finish Thickness	10μin (0.25μm)
Contact Finish	Gold
Contact Material	Phosphor Bronze
Termination	Wire Wrap
Mounting Type	Board Edge, Straddle Mount
Features	Card Extender
Pitch	0.156" (3.96mm)
Number of Rows	2
Card Thickness	0.062" (1.57mm)
Number of Positions	80
Number of Positions/Bay/Row	40
Gender	Female
Card Type	Non Specified - Dual Edge
Series	-
Package	-
	Card Edge Connectors - Edgeboard Connectors
Category	Connectors, Interconnects
Manufacturer	Sullins Connector Solutions
Manufacturer Part Number	GSM40DRMT-S288

#### **GSM40DRMT-S288 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GSM40DRMT-S288 Payment Methods**



















## **GSM40DRMT-S288 Shipping Methods**













If you have any question about GSM40DRMT-S288, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com