



Heisener.com

GTC01F-10SL-3S(G96) Information

Part Number GTC01F-10SL-3S(G96)

Manufacturer Amphenol Industrial Operations

Connectors, Interconnects Category

Circular Connectors

CONN RCPT 3POS INLINE SKT **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GTC01F-10SL-3S(G96) Specifications

Manufacturer Part Number GTC01F-10SL-3S(G96) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 10SL-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 10SL-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Cable Clamp Voltage - Rated Current Rating -	Manufacturer Part Number	GTC01F-10SL-3S(G96)
Package-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert10SL-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 10SL-3 Shell Size, MIL - Champan Growth Growt	Category	Connectors, Interconnects
Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 10SL-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert10SL-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions3Shell Size - Insert10SL-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	GT, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	10SL-3
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating IP67 - Dust Tight, Waterproof Aluminum, Anodic Coating (Alumilite) Silver Cable Clamp	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating	Orientation	N (Normal)
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Cable Clamp
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

GTC01F-10SL-3S(G96) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GTC01F-10SL-3S(G96) Payment Methods





















GTC01F-10SL-3S(G96) Shipping Methods













If you have any question about GTC01F-10SL-3S(G96), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com