

GTC02R-28-3S Information

Heisener.com

Part Number GTC02R-28-3S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN RCPT 3POS BOX MNT W/SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GTC02R-28-3S Specifications

Manufacturer Part Number GTC02R-28-3S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 28-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 28-3 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Lock 1250VAC, 1750VDC Current Rating -	Manufacturer Part Number	GTC02R-28-3S
Circular Connectors Package - Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 28-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Luck Lize Orientation 1250VAC, 1750VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 28-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating	Category	Connectors, Interconnects
Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 28-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert28-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-	Package	-
Number of Positions3Shell Size - Insert28-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-	Series	GT, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Number of Positions	3
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-	Shell Size - Insert	28-3
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated 5 Silver	Orientation	N (Normal)
Contact Finish Features - Voltage - Rated Current Rating Silver - - 1250VAC, 1750VDC -	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 1250VAC, 1750VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	1250VAC, 1750VDC
Report errors?	Current Rating	-
		Report errors?

GTC02R-28-3S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GTC02R-28-3S Payment Methods



















GTC02R-28-3S Shipping Methods













If you have any question about GTC02R-28-3S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com