



Heisener.com

GTC030F-24-27S(A24) Information

Part Number GTC030F-24-27S(A24)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 7POS PNL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GTC030F-24-27S(A24) Specifications

Manufacturer Part NumberGTC030F-24-27S(A24)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-27Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable ClampVoltage - Rated1250VAC, 1750VDC		
Category Connectors, Interconnects Circular Connectors Package - Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 24-27 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated Connectors, Interconnects Circular Connectors ATTENDACTOR OF TABLE OF TA	Manufacturer Part Number	GTC030F-24-27S(A24)
Package-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert24-27Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable ClampVoltage - Rated1250VAC, 1750VDC	Manufacturer	Amphenol Industrial Operations
Package - GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 24-27 Shell Size, MIL - Crimp Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Category	Connectors, Interconnects
Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 24-27 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 24-27 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Package	-
Number of Positions Shell Size - Insert 24-27 Shell Size, MIL Mounting Type Panel Mount, Flange Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Voltage - Rated 7 Austrian Aust	Series	GT, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Number of Positions	7
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable ClampVoltage - Rated1250VAC, 1750VDC	Shell Size - Insert	24-27
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Termination	Crimp
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable ClampVoltage - Rated1250VAC, 1750VDC	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Cable Clamp Voltage - Rated Aluminum, Olive Drab Cadmium Plated Gold 1250VAC, 1750VDC	Orientation	N (Normal)
Contact Finish Gold Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Cable Clamp Voltage - Rated 1250VAC, 1750VDC	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 1250VAC, 1750VDC	Contact Finish	Gold
	Features	Cable Clamp
	Voltage - Rated	1250VAC, 1750VDC
Current Rating -	Current Rating	-
Report errors?		Report errors?

GTC030F-24-27S(A24) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GTC030F-24-27S(A24) Payment Methods



















GTC030F-24-27S(A24) Shipping Methods













If you have any question about GTC030F-24-27S(A24), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com