



Heisener.com

GTC06AF-32-22S(G96) Information

Part Number GTC06AF-32-22S(G96)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 54POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GTC06AF-32-22S(G96) Specifications

Manufacturer Part Number GTC06AF-32-22S(G96) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series GT, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 54 Shell Size - Insert 32-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	GTC06AF-32-22S(G96)
Package-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesGT, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 32-22 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Series	GT, MIL-5015 Derivative
Shell Size - Insert32-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Cable Clamp Voltage - Rated Souvac, 700VDC Current Rating -	Number of Positions	54
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	32-22
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating	Orientation	N (Normal)
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating	Ingress Protection	-
Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Cable Clamp
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

GTC06AF-32-22S(G96) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GTC06AF-32-22S(G96) Payment Methods



















GTC06AF-32-22S(G96) Shipping Methods













If you have any question about GTC06AF-32-22S(G96), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com