



GTC06F28-6S(RDS)(025) Information



For Reference Only

Part Number GTC06F28-6S(RDS)(025)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG FREE/HANG 3POS SIZE 4

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GTC06F28-6S(RDS)(025) Specifications

Manufacturer Part Number GTC06F28-6S(RDS)(025) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series Amphe-Power? GT, Radsok? Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 28-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zine Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A		
CategoryConnectors, InterconnectsPackage-SeriesAmphe-Power? GT, Radsok?Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating120A	Manufacturer Part Number	GTC06F28-6S(RDS)(025)
Package-SeriesAmphe-Power? GT, Radsok?Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating120A	Manufacturer	Amphenol Industrial Operations
Package - Series Amphe-Power? GT, Radsok? Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 28-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Category	Connectors, Interconnects
SeriesAmphe-Power? GT, Radsok?Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating120A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating120A	Package	-
Number of Positions3Shell Size - Insert28-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating120A	Series	Amphe-Power? GT, Radsok?
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating	Number of Positions	3
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Shell Size - Insert	28-6
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Cable Clamp Voltage - Rated Current Rating Aluminum, Black Zinc Cobalt Plated Cobalt Plated Silver Cable Clamp 120A	Orientation	N (Normal)
Contact Finish Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 120A	Contact Finish	Silver
Current Rating 120A	Features	Cable Clamp
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	120A
		Report errors?

GTC06F28-6S(RDS)(025) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GTC06F28-6S(RDS)(025) Payment Methods



















GTC06F28-6S(RDS)(025) Shipping Methods













If you have any question about GTC06F28-6S(RDS)(025), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com