

GTC06G-36-10P(125) Information

Heisener.com

GTC06G-36-10P(125) Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

CONN PLUG 48POS INLINE PIN **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GTC06G-36-10P(125) Specifications

Manufacturer Part Number GTC06G-36-10P(125) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series GT, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 48 Shell Size - Insert 36-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish - Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series GT, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 48 Shell Size - Insert 36-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish - Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating Connectors, Interconnects Circular Connectors Gircular Connectors FT, MIL -5015 Derivative FURL -5015 Derivative Full -5015 Derivative Full -5015 Derivative As A	Manufacturer Part Number	GTC06G-36-10P(125)
Package-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, Finish-Contact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, Finish-Contact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
Series GT, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 48 Shell Size - Insert 36-10 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish - Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions48Shell Size - Insert36-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, Finish-Contact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 36-10 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish - Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated Current Rating - Shell Material, Finish - Course ShovaC, 700VDC Current Rating	Series	GT, MIL-5015 Derivative
Shell Size - Insert36-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, Finish-Contact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating-	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish - Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	48
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, Finish-Contact FinishGoldFeaturesShrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	36-10
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish - Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish - Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish - Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated Current Rating	Orientation	N (Normal)
Contact Finish Gold Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	-
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shrink Boot Adapter
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

GTC06G-36-10P(125) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GTC06G-36-10P(125) Payment Methods

































If you have any question about GTC06G-36-10P(125), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com