



GTS02R-18-19S Information

Heisener.com

Part Number GTS02R-18-19S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 10POS BOX MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GTS02R-18-19S Specifications

Manufacturer Part Number Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Package Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating -		
CategoryConnectors, InterconnectsPackage-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert18-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	GTS02R-18-19S
Package-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert18-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Category	Connectors, Interconnects
Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 10 Shell Size - Insert 18-19 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert18-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions10Shell Size - Insert18-19Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Series	GT, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	10
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	18-19
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Silver - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Features - Voltage - Rated Current Rating Silver - 500VAC, 700VDC -	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	500VAC, 700VDC
	Current Rating	-
Report errors?		Report errors?

GTS02R-18-19S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GTS02R-18-19S Payment Methods



















GTS02R-18-19S Shipping Methods













If you have any question about GTS02R-18-19S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com