

# GTS030-20-16S Information

Heisener.com

Part Number GTS030-20-16S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN RCPT 9POS PNL MNT SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **GTS030-20-16S Specifications**

Manufacturer Part Number     GTS030-20-16S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     GT, MIL-5015 Derivative       Connector Type     Receptacle, Female Sockets       Number of Positions     9       Shell Size - Insert     20-16       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Solder Cup       Fastening Type     Reverse Bayonet Lock       Orientation     N (Normal)       Ingress Protection     IP67 - Dust Tight, Waterproof       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Rating     -       Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	GTS030-20-16S
Package-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
Series GT, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size - Insert 20-16 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Series	GT, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	9
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	20-16
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Silver  -  -  -  -  -  -  -  -  -  -  -  -  -	Orientation	N (Normal)
Contact Finish  Features  - Voltage - Rated  Current Rating  Silver  -  500VAC, 700VDC  -	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

#### GTS030-20-16S Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GTS030-20-16S Payment Methods**



















### **GTS030-20-16S Shipping Methods**













If you have any question about GTS030-20-16S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com