



### **GTS06AF-16-11S Information**

Heisener.com

Part Number GTS06AF-16-11S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 2POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **GTS06AF-16-11S Specifications**

| Manufacturer Part Number     GTS06AF-16-11S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     GT, MIL-5015 Derivative       Connector Type     Plug, Female Sockets       Number of Positions     2       Shell Size - Insert     16-11       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Reverse Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     Cable Clamp       Voltage - Rated     500VAC, 700VDC       Current Rating     -       Report errors? |                          |                                     |
|--|--------------------------|-------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-   | Manufacturer Part Number | GTS06AF-16-11S                      |
| Package-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-  | Manufacturer             | Amphenol Industrial Operations      |
| Package-SeriesGT, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-  | Category                 | Connectors, Interconnects           |
| Series GT, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 16-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -   |                          | Circular Connectors                 |
| Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-   | Package                  | -                                   |
| Number of Positions2Shell Size - Insert16-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-   | Series                   | GT, MIL-5015 Derivative             |
| Shell Size - Insert Shell Size, MIL  | Connector Type           | Plug, Female Sockets                |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating -   | Number of Positions      | 2                                   |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating-   | Shell Size - Insert      | 16-11                               |
| Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -   | Shell Size, MIL          | -                                   |
| Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -  | Mounting Type            | Free Hanging (In-Line)              |
| Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating -   | Termination              | Solder Cup                          |
| Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating -   | Fastening Type           | Reverse Bayonet Lock                |
| Shell Material, Finish  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Silver  Cable Clamp   | Orientation              | N (Normal)                          |
| Contact Finish  Features  Cable Clamp  Voltage - Rated  Current Rating   | Ingress Protection       | -                                   |
| Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating -   | Shell Material, Finish   | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 500VAC, 700VDC  Current Rating -   | Contact Finish           | Silver                              |
| Current Rating -   | Features                 | Cable Clamp                         |
|  | Voltage - Rated          | 500VAC, 700VDC                      |
| Report errors?   | Current Rating           | -                                   |
|  |                          | Report errors?                      |

#### **GTS06AF-16-11S Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GTS06AF-16-11S Payment Methods**





















## **GTS06AF-16-11S Shipping Methods**













If you have any question about GTS06AF-16-11S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com