

# **GURB5H60HE3/45**

#### **GURB5H60HE3/45** Information

ww.heisener.com	 GURB5H60HE3/45 Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE GEN PURP 600V 5A TO263AB TO-263-3, D2Pak (2 Leads + Tab), TO-263AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **GURB5H60HE3/45** Specifications

ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.8V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)30nsCurrent - Reverse Leakage @ Vr20µA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABPackage-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.8V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (ttr)30nsCurrent - Reverse Leakage @ Vr20µA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	GURB5H60HE3/45
Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.8V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)30nsCurrent - Reverse Leakage @ Vr $20\mu A @ 600V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.8V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)30nsCurrent - Reverse Leakage @ Vr $20\mu A @ 600V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction $-55^{\circ}$ C ~ 150°C	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max) $600V$ Current - Average Rectified (Io) $5A$ Voltage - Forward (Vf) (Max) @ If $1.8V @ 5A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr) $30ns$ Current - Reverse Leakage @ Vr $20\muA @ 600V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max) $600V$ Current - Average Rectified (Io) $5A$ Voltage - Forward (Vf) (Max) @ If $1.8V @ 5A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $30ns$ Current - Reverse Leakage @ Vr $20\mu A @ 600V$ Capacitance @ Vr, F $-$ Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Voltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.8V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)30nsCurrent - Reverse Leakage @ Vr20µA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Series	-
Current - Average Rectified (Io)5AVoltage - Forward (Vf) (Max) @ If1.8V @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)30nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.8V @ 5A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $30ns$ Current - Reverse Leakage @ Vr $20\mu A @ 600V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	600V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)30nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	5A
Reverse Recovery Time (trr)30nsCurrent - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.8V @ 5A
Current - Reverse Leakage @ Vr20μA @ 600VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	30ns
Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	20µA @ 600V
Package / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device PackageTO-263ABOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
	Supplier Device Package	TO-263AB
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

#### **GURB5H60HE3/45** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **GURB5H60HE3/45** Payment Methods





If you have any question about GURB5H60HE3/45, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com