

GX-N30M Information



For Reference Only

Part Number GX-N30M

Manufacturer Panasonic Industrial Automation Sales

Category Sensors, Transducers

Proximity Sensors

Description SENSOR PROX NPN 8MM 12-24VDC

Package Cylinder, Threaded - M30

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









GX-N30M Specifications

Manufacturer Part NumberGX-N30MManufacturerPanasonic Industrial Automation SalesCategorySensors, TransducersPackageCylinder, Threaded - M30SeriesGXSensor TypeInductiveSensing Distance0.315" (8mm)Output TypeNPN-NO, 3-WireResponse Frequency300HzShieldingShieldedMaterial - BodyNickel-Plated BrassVoltage - Supply12 V ~ 24 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30Report errors?		
Category Sensors, Transducers Proximity Sensors Package Cylinder, Threaded - M30 Series GX Sensor Type Inductive Sensing Distance 0.315" (8mm) Output Type NPN-NO, 3-Wire Response Frequency 300Hz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Operating Temperature 1-25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Manufacturer Part Number	GX-N30M
Proximity Sensors Package Cylinder, Threaded - M30 Series GX Sensor Type Inductive Sensing Distance 0.315" (8mm) Output Type NPN-NO, 3-Wire Response Frequency 300Hz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Manufacturer	Panasonic Industrial Automation Sales
Package Cylinder, Threaded - M30 Series GX Sensor Type Inductive Sensing Distance 0.315" (8mm) Output Type NPN-NO, 3-Wire Response Frequency 300Hz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Category	Sensors, Transducers
Series GX Sensor Type Inductive Sensing Distance 0.315" (8mm) Output Type NPN-NO, 3-Wire Response Frequency 300Hz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30		Proximity Sensors
Sensor Type Sensing Distance Output Type NPN-NO, 3-Wire Response Frequency Shielding Shielded Material - Body Voltage - Supply Termination Style Operating Temperature Ingress Protection Indicator Package / Case Inductive INPN-NO, 3-Wire NPN-NO, 3-Wire Shielded NPN-NO, 3-Wire NPN-NO, 3-Wire Supply 12 V ~ 24 V Shielded Cable Brass Vickel-Plated Brass Cable Leads Cable Leads Cable Leads Cable Leads Cylinder, Threaded - M30	Package	Cylinder, Threaded - M30
Sensing Distance 0.315" (8mm) Output Type NPN-NO, 3-Wire Response Frequency 300Hz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Series	GX
Output Type Response Frequency 300Hz Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection Indicator LED Package / Case NPN-NO, 3-Wire 300Hz Shielded Cable Leads Nickel-Plated Brass LED Cylinder, Threaded - M30	Sensor Type	Inductive
Response Frequency Shielding Shielded Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Sensing Distance	0.315" (8mm)
Shielding Material - Body Nickel-Plated Brass Voltage - Supply 12 V ~ 24 V Termination Style Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Shielded Nickel-Plated Brass 12 V ~ 24 V Cable Leads Cable Leads -25°C ~ 70°C IP67 Cylinder, Threaded - M30	Output Type	NPN-NO, 3-Wire
Material - BodyNickel-Plated BrassVoltage - Supply12 V ~ 24 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Response Frequency	300Hz
Voltage - Supply Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Shielding	Shielded
Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Material - Body	Nickel-Plated Brass
Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Voltage - Supply	12 V ~ 24 V
Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M30	Termination Style	Cable Leads
Indicator LED Package / Case Cylinder, Threaded - M30	Operating Temperature	-25°C ~ 70°C
Package / Case Cylinder, Threaded - M30	Ingress Protection	IP67
	Indicator	LED
Report errors?	Package / Case	Cylinder, Threaded - M30
		Report errors?

GX-N30M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

GX-N30M Payment Methods



















GX-N30M Shipping Methods













If you have any question about GX-N30M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com