

H10B-SDR-LB-2PG16

H10B-SDR-LB-2PG16 Information



For Reference Only

Part Number H10B-SDR-LB-2PG16

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

Description CONN BASE SIDE DUAL SZ10B PG16

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









H10B-SDR-LB-2PG16 Specifications

Manufacturer Part NumberH10B-SDR-LB-2PG16ManufacturerTE Connectivity AMP ConnectorsCategoryConnectors, InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesHBConnector TypeBase - Box MountStyleSide Entry, DualSize10BLock LocationLocking Clip (1) on Base BottomThread SizePG16Size / Dimension3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm)Housing ColorGrayFeaturesCover, Feed ThroughIngress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°CReport errors?			
Category Connectors, Interconnects Heavy Duty Connectors - Housings, Hoods, Bases Package - Series HB Connector Type Base - Box Mount Style Side Entry, Dual Size 10B Lock Location Locking Clip (1) on Base Bottom Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Manufacturer Part Number	H10B-SDR-LB-2PG16	
Package - Series HB Connector Type Base - Box Mount Style Side Entry, Dual Size 10B Lock Location Locking Clip (1) on Base Bottom Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Manufacturer	TE Connectivity AMP Connectors	
Package - Series HB Connector Type Base - Box Mount Style Side Entry, Dual Size 10B Lock Location Locking Clip (1) on Base Bottom Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Category	Connectors, Interconnects	
Series HB Connector Type Base - Box Mount Style Side Entry, Dual Size 10B Lock Location Locking Clip (1) on Base Bottom Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C		Heavy Duty Connectors - Housings, Hoods, Bases	
Connector Type Base - Box Mount Style Side Entry, Dual Size 10B Lock Location Locking Clip (1) on Base Bottom Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Package	-	
Style Side Entry, Dual Size 10B Lock Location Locking Clip (1) on Base Bottom Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Series	НВ	
Size 10B Lock Location Locking Clip (1) on Base Bottom Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Connector Type	Base - Box Mount	
Lock LocationLocking Clip (1) on Base BottomThread SizePG16Size / Dimension3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm)Housing ColorGrayFeaturesCover, Feed ThroughIngress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Style	Side Entry, Dual	
Thread Size PG16 Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size	10B	
Size / Dimension 3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm) Housing Color Gray Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Lock Location	Locking Clip (1) on Base Bottom	
Housing ColorGrayFeaturesCover, Feed ThroughIngress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialAluminum Alloy, Die CastHousing FinishPowder CoatedOperating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Thread Size	PG16	
Features Cover, Feed Through Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Size / Dimension	3.701" L x 2.047" W x 2.386" H (94.00mm x 52.00mm x 60.60mm)	
Ingress Protection IP65 - Dust Tight, Water Resistant Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Housing Color	Gray	
Housing Material Aluminum Alloy, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	Cover, Feed Through	
Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Ingress Protection	IP65 - Dust Tight, Water Resistant	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Material	Aluminum Alloy, Die Cast	
	Housing Finish	Powder Coated	
Report errors?	Operating Temperature	-40°C ~ 125°C	
			Report errors?

H10B-SDR-LB-2PG16 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

H10B-SDR-LB-2PG16 Payment Methods



















H10B-SDR-LB-2PG16 Shipping Methods













If you have any question about H10B-SDR-LB-2PG16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com