

HBC06DRYS-S93

HBC06DRYS-S93 Information

Heisener.com	Part Number Manufacturer Category Description Package	HBC06DRYS-S93 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 12POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HBC06DRYS-S93 Specifications

Manufacturer Part Number HBC06DRYS-S93 Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Card Edge Connectors - Edgeboard Connectors Package - Stries - Gard Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions/Bay/Row 12 Number of Rows 2 Pictures 0.0090" (2.36mm) Number of Rows 2 Pictures 0.100" (2.54mm) Mounting Type Solder Contact Material Solder Contact Material Solder Contact Finish Thickness Gold Contact Finish Thickness Gold Contact Finish Thickness Jupin (0.25µm) Contact Finish Thickness Bill Bellows Contact Finish Thickness Gold Contact Finish Thickness Bill Bellows Color Bue Falage Feature SideMount Openin	_	
CategoryConnectors InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Card Thickness12Number of Rows2Pitch0.100° (2.54mm)Number of Rows0.100° (2.54mm)Features-Nongh HoleSolderContact MaterialSolderContact FinishGoldContact Finish ThicknessIpin (0.25µm)Contact TypeFull BellowsContact TypeSull BellowsContact SeriesSull BellowsContact TypeSull BellowsContact TypeSull BellowsContact TypeSull BellowsContact TypeSull BellowsContact TypeSull SeriesContact TypeSull SeriesCo	Manufacturer Part Number	HBC06DRYS-S93
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Card Thickness0.903° (2.36mm)Card Thickness0.903° (2.36mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeFinough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessIpin (0.25µm)Contact TypeHule IncompetingContact TypeSolderContact TypeSolderContact Finish ThicknessIpin (0.25µm)ColorBueFauresSide Mount Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature- 65° C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeFolderContact MaterialSolderContact Finish Thickness10jui (0.25µm)Contact Finish Thickness10jui (0.25µm)Contact Finish Thickness10jui (0.25µm)Contact Finish Thickness10jui (0.25µm)Contact Finish Thickness10jui (0.25µm)ColorBueFinage FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFaqueresSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIujin (0.25µm)Contact TypeFull BellowsColorBueFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating TemperatureSide Yange Y	Package	-
GenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact Finish Thickness5uleColorBuleFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row6Number of Positions12Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type0.100" (2.54mm)TerminationSolderContact MaterialBeryllium CopperContact Finish Thickness0.juli (0.25µm)Contact TypeFul BellowsColorBueFlange FeatureSider Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating TemperatureSiC ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 12 Card Thickness 0.093" (2.36mm) Number of Rows 2 Number of Rows 0.100" (2.54mm) Features - Mounting Type Through Hole Nonder Adderial Solder Contact Material Beryllium Copper Contact Finish Thickness Ioluin (0.25µm) Contact Type Full Bellows Color Bue Fange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature 65°C ~ 125°C	Gender	Female
Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Mounting Type Solder Termination Solder Contact Material Beryllium Copper Contact Finish Thickness Gold Contact Type Full Bellows Color Bue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Positions/Bay/Row	6
Number of Rows2Nitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	12
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorBueFange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.093" (2.36mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeFul BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$
		Report errors?

HBC06DRYS-S93 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HBC06DRYS-S93 Payment Methods



If you have any question about HBC06DRYS-S93, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com