

# **HBC10HETN**

## **HBC10HETN Information**

Heisener.com	 HBC10HETN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 10POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **HBC10HETN Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row0062° (1.57mm)Number of Rows1Number of Rows1Pictures-Number of Rows1Pictures-Nongh HoleSolderContact MaterialSolderContact Finish ThicknessGoldContact TypeInpin (2.5µm)Contact TypeGoldContact TypeGoldContact TypeContact SolderContact Finish ThicknessSolderContact TypeSolderContact TypeSolderContact TypeContactionContact TypeSolderContact TypeSolder <th>-</th> <th></th>	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Nounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µín (0.25µm)Contact TypeCantileverContact TypeGoldContact TypeCantileverContact TypeCantileverContact Type-Contact TypeCantileverColor-Fauge Feature-Operating Temperature-Soler Cal25°C-	Manufacturer Part Number	HBC10HETN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10/uin (0.25µm)Contact Finish Thickness10/uin (0.25µm)Contact TypeCantileverContact TypeCantileverColor-Flange Feature-Operating Temperature-5°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness10/uin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row10Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeGoldContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row10Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact Type-Features-Solder10µin (0.25µm)Contact Finish Thickness-Contact Type-Feature-Color-Flange Feature-Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row-Number of Positions10Card Thickness0.602° (1.57mm)Number of Rows1Pitch0.100° (2.54mm)Pitch-Mounting Type-Mounting TypeSolderContact FinishGoldContact Finish ThicknessGoldContact Finish Thickness-Contact Finish Thickness-Color-Finige Feature-Pining Feature-Coperating Thickness-Color-Color-Fining Feature-Operating Temperature-Contact Finish-Color- <td< td=""><td>Series</td><td>-</td></td<>	Series	-
Number of Positions/Bay/Row-Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness0.101" (0.25µm)Contact TypeCantileverColor-Flange Feature-Pinge Feature-Operating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessI0µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-Solor Cantar Science-Science-Color-Science	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	10
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Color-Color-Flange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessI/lµin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Rows	1
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color -   Flange Feature -   Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **HBC10HETN Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HBC10HETN Payment Methods**



# **HBC10HETN Shipping Methods**



If you have any question about HBC10HETN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com