

# **HBC26DEYN**

#### **HBC26DEYN Information**

Heisener.com	Part Number Manufacturer Category Description Package	HBC26DEYN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 52POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **HBC26DEYN Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type100 (2.54mm)Contact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeCandieverContact TypeCandieverC	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions/Bay/Row0.062" (1.57mm)Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Nounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeGoldContact TypeCantileverContact Finish Thickness0.92µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-Solor Cal25°C-	Manufacturer Part Number	HBC26DEYN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverColor-Flange Feature-Operating Temperature-5°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness10/µin (0.25µm)Contact TypeCantileverContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeGoldContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeMong HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessJuni (0.25µm)Contact Finish ThicknessGoldContact Finish ThicknessSolderColorJuni (0.25µm)ColorSolderColor <t< td=""><td>Series</td><td>-</td></t<>	Series	-
Number of Positions/Bay/Row26Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-Operating Temperature-Contact Spece-Contact Spece-Color <t< td=""><td>Card Type</td><td>Non Specified - Dual Edge</td></t<>	Card Type	Non Specified - Dual Edge
Number of Positions52Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessI0µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-Operating Temperature-	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	26
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	52
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Color-Color-Flange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessI/lµin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperatures-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color -   Flange Feature -   Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **HBC26DEYN** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **HBC26DEYN** Payment Methods



### **HBC26DEYN Shipping Methods**



If you have any question about HBC26DEYN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com