

HBC35DEYN

uest a Quote

HBC35DEYN Information

Part Number	HBC35DEYN
Manufacturer	Sullins Connector Solutions
Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
Description Package	CONN EDGE DUAL FMALE 70POS 0.100
	-
	For the pricing/inventory/lead time, please contact
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com
	Manufacturer Category Description

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HBC35DEYN Specifications

ManufacturerSullins Connector SolutionsCardectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions0.062" (1.57mm)Number of Rows2Pictures0.100" (2.54mm)Number of Rows2PicturesSolderContact MaterialSolderContact FinishGoldContact Finish ThicknessIpin (0.25µm)Contact TypeGuid (0.25µm)Contact TypeGuid (0.25µm)Contact Finish ThicknessSolderContact Finish ThicknessIpin (0.25µm)Contact TypeGuid (0.25µm)Contact TypeGuid (0.25µm)Contact Finish ThicknessSolderContact Finish ThicknessIpin (0.25µm)Contact TypeCantileverContact Type	-	
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions/Bay/Row0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeGoldContact TypeCantileverContact TypeCantileverColor-Flange Feature-Color-Flange Feature-Operating Temperature65°C ~ 125°C	Manufacturer Part Number	HBC35DEYN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Finish ThicknessGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeCantileverContact TypeGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness0.10µí (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeMong HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessJupin (0.25µm)Contact Finish ThicknessJupin (0.25µm)Contact Finish ThicknessSolderContact Finish ThicknessGoldContact Finish ThicknessSolderContact Finish ThicknessSolderSolderSolderContact Finish ThicknessSolderSolderSolderContact Finish ThicknessSolderSolderSolderSolderSolderSolderSolderSolderSolderSolderSolderSolderSolder<	Series	-
Number of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-S°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessIupin (0.25µm)Contact TypeCantileverFlange Feature-Operating Temperature65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	35
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	70
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Color-Color-Flange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

HBC35DEYN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HBC35DEYN Payment Methods



HBC35DEYN Shipping Methods



If you have any question about HBC35DEYN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com