

## **HBC44DRYN**

#### **HBC44DRYN Information**

Heisener.com	 HBC44DRYN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 88POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **HBC44DRYN Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIujui (0.25µm)Contact TypeHul BellowsContact TypeSolderContact TypeSolderContac		
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions/Bay/Row0.062" (1.57mm)Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Nounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSulle Contact TypeContact TypeSulle Contact Type <trt< td=""><td>Manufacturer Part Number</td><td>HBC44DRYN</td></trt<>	Manufacturer Part Number	HBC44DRYN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact Type50lderContact Type50lderContact Type50lderContact Type50lderContact Type60dContact Type60dContact Type50ldersContact Type50ldersContact Type60ldContact Type60ldContact Type60ldContact Type60leContact Type	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness10/uin (0.25µm)Contact TypeFull BellowsContact Type50lderContact Type50lderContact Type10/uin (0.25µm)Contact Type50lderContact Type50lderContact Type60ldContact Type60ldContact Type50lderContact Type50lderContact Type60ldContact Type60ldContact Type60ldContact Type60leColorBlueFinage Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions/Bay/Row88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish ThicknessGoldContact Finish ThicknessIlpuin (0.25µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessFull BellowsContact TypeFull BellowsColorBueFage Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact FinishFold (0.52µm)Contact Finish ThicknessIpµin (0.25µm)Contact Finish ThicknessFull BellowsColorBueFlange Feature-Operating Temperature-6°C~ 125°C	Series	-
Number of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type1hrough HoleTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature50°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessI0µin (0.25µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-55°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	44
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	88
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueColorBlueFlange Feature-Operating Temperature-55°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessI/lµin (0.25µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-55°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Blue   Flange Feature -   Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	-
Report errors?	Operating Temperature	$-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$
		Report errors?

#### **HBC44DRYN** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HBC44DRYN** Payment Methods



### **HBC44DRYN Shipping Methods**



If you have any question about HBC44DRYN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com