

HBC44HETN

uest a Quote

HBC44HETN Information

Heisener.com	Part Number	HBC44HETN	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 44POS 0.100	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HBC44HETN Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeContact SpecifiesContact TypeContact SpecifiesContact TypeContact SpecifiesContact TypeContact SpecifiesContact TypeContact SpecifiesContact TypeContact SpecifiesContact TypeSolderContact TypeContact SpecifiesContact TypeScattieverContact TypeScattiever	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessIQuin (0.25µm)Contact Finish ThicknessIQuin (0.25µm)Contact TypeCantileverContact TypeCantileverContact Finish ThicknessIQuin (0.25µm)Contact TypeCantileverContact TypeSolderContact TypeCantileverColor-Flange Feature-Operating Temperature-Solder-Contact TypeCantileverColor-Flange Feature-Color-Flange Feature-Contact TypeCantileverContact Type-Color-Flange Feature-Color-Flange Feature-Color-Flange Feature-Color-Color-Color-Flange Feature-Color-Color-Color-Color-Color	Manufacturer Part Number	HBC44HETN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness10/uin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverContact TypeCantileverContact Type-Color-Flange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10/uin (0.25µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverContact TypeCantileverContact Type-Flange Feature-Operating Temperature-50°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions/Bay/Row44Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeGoldContact TypeGoldContact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row-Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows1Number of Rows0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeMough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessIupin (0.25µm)Contact TypeCantileverColor-Flarge Feature-Operating Temperature-Operating Temperature-Operature-Operature-Operature-Operature-Operature-Operature-Operature-Operature-<	Series	-
Number of Positions/Bay/Row-Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows1Number of Rows0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Type10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-Solor-Solor-Color-Flange Temperature-Operating Temperature-Solor-Contact Solor-Solor-Color-Solor- <t< td=""><td>Card Type</td><td>Non Specified - Dual Edge</td></t<>	Card Type	Non Specified - Dual Edge
Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish ThicknessIupin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-Operating Temperature-Operating Temperature-Operating Temperature-Solor Carl Sc-Operating Temperature-Operating Temperature-Sc-Operating Temperature-Sc-Sc-Contact Sc-Sc	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	44
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Color-Color-Flange Feature-Operating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact Type-Color-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Rows	1
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

HBC44HETN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HBC44HETN Payment Methods



HBC44HETN Shipping Methods



If you have any question about HBC44HETN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com