



HBC60DREN Information

Heisener.com

Part Number HBC60DREN

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 120POS .100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HBC60DREN Specifications

Manufacturer Part Number HBC60DREN Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	TID COOD REAL OPECHICATIONS	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	HBC60DREN
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row 60 Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row Number of Positions 120 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature 65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions120Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	60
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	120
Pitch 0.100" (2.54mm) Features - Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Free Hanging (In-Line) Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Blue Flange Feature Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeFree Hanging (In-Line)TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
Termination Solder Eyelet(s) Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeFull BellowsColorBlueFlange Feature-Operating Temperature -65° C ~ 125° C	Mounting Type	Free Hanging (In-Line)
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature Gold $10\mu in (0.25\mu m)$ Full Bellows $-65^{\circ}C \sim 125^{\circ}C$	Termination	Solder Eyelet(s)
Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Full Bellows Color Blue Flange Feature - 65° C ~ 125° C	Contact Material	Beryllium Copper
Contact Type Full Bellows Color Blue Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color Blue Flange Feature - $65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness	10μin (0.25μm)
Flange Feature - Generating Temperature -65°C ~ 125 °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

HBC60DREN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HBC60DREN Payment Methods





















HBC60DREN Shipping Methods













If you have any question about HBC60DREN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com