



#### **HC2E-H-DC6V Information**



For Reference Only

Part Number HC2E-H-DC6V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GENERAL PURPOSE DPDT 3A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **HC2E-H-DC6V Specifications**

Manufacturer       HC2E-H-DC6V         Manufacturer       Panasonic Electric Works         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       HCE         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       150mA         Coil Voltage       6VDC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       3A         Switching Voltage       250VAC - Max         Turn On Voltage (Max)       4.8 VDC         Turn Off Voltage (Min)       0.6 VDC         Operate Time       10ms         Release Time       5ms         Features       Sealed - Amber         Mounting Type       Socketable         Termination Style       Plug In		
CategoryRelaysPackage-SeriesHCERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current150mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesSealed - AmberMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	HC2E-H-DC6V
Package-SeriesHCERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current150mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesSealed - AmberMounting TypeSocketableTermination StylePlug In	Manufacturer	Panasonic Electric Works
Package         -           Series         HCE           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         150mA           Coil Voltage         6VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         3A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         4.8 VDC           Turn Off Voltage (Min)         0.6 VDC           Operate Time         10ms           Release Time         5ms           Features         Sealed - Amber           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesHCERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current150mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesSealed - AmberMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 150mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Sealed - Amber Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current150mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage250VAC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesSealed - AmberMounting TypeSocketableTermination StylePlug In	Series	HCE
Coil Current 150mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Sealed - Amber Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 3A Switching Voltage 250VAC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Sealed - Amber Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current) 3A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Amber  Mounting Type Socketable  Termination Style Plug In	Coil Current	150mA
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  4.8 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Amber  Mounting Type  Socketable  Termination Style	Coil Voltage	6VDC
Switching Voltage 250VAC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Amber  Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Oe VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Amber  Mounting Type  Socketable  Termination Style  4.8 VDC	Contact Rating (Current)	3A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Sealed - Amber  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC - Max
Operate Time 10ms Release Time 5ms Features Sealed - Amber Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	4.8 VDC
Release Time 5ms Features Sealed - Amber Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	0.6 VDC
Features Sealed - Amber  Mounting Type Socketable  Termination Style Plug In	Operate Time	10ms
Mounting Type Socketable Termination Style Plug In	Release Time	5ms
Termination Style Plug In	Features	Sealed - Amber
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
report errors.		Report errors?

#### **HC2E-H-DC6V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HC2E-H-DC6V Payment Methods**



















### **HC2E-H-DC6V Shipping Methods**













If you have any question about HC2E-H-DC6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com