

HCC05DREH-S13

a Quote

HCC05DREH-S13 Information

| Heisener.com | Part Number | HCC05DREH-S13 | |
|--------------------|--------------|---|--------------|
| | Manufacturer | Sullins Connector Solutions | |
| | Category | Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors | 8 |
| | Description | CONN EDGE DUAL FMALE 10POS 0.100 | - 1 1 |
| | Package | - | |
| | | For the pricing/inventory/lead time, please contact | |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Re |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HCC05DREH-S13 Specifications

| Manufacturer Part NumberHCC05DREH-S13ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions/Bay/Row0062" (1.57mm)Card Type0.062" (1.57mm)Number of Rows2Features0.010" (2.54mm)FeaturesSolide Edge Straddle MountMounting TypeBoard Edge, Straddle MountContact FinishGoldContact Finish ThicknessGoldContact TurneSuljin (0.76µm) | | | |
|--|-----------------------------|--|--|
| CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions0.062° (1.57mm)Card Thickness0.062° (1.57mm)Number of Rows2FeaturesCard Edge, Straddle MountMounting TypeSolar Edge, Straddle MountTerminationSolde Edge, Straddle MountContact MaterialGoldContact FinishGoldSolar Of Specific Straddle MountContact Finish ThicknessSolyin (0.76µm) | Manufacturer Part Number | HCC05DREH-S13 | |
| Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm) | Manufacturer | Sullins Connector Solutions | |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions/Bay/Row10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldSoluen CoppenSoluen CoppenContact Finish ThicknessSoluen CoppenSoluen | Category | Connectors, Interconnects | |
| Series-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldSolyin (0.76µm)30µin (0.76µm) | | Card Edge Connectors - Edgeboard Connectors | |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness3µin (0.76µm) | Package | - | |
| GenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm) | Series | - | |
| Number of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness30µin (0.76µm) | Card Type | Non Specified - Dual Edge | |
| Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm) | Gender | Female | |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm) | Number of Positions/Bay/Row | 5 | |
| Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldSoluin (0.76µm)30µin (0.76µm) | Number of Positions | 10 | |
| Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldStore Spin (0.76µm)Super (S) | Card Thickness | 0.062" (1.57mm) | |
| FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm) | Number of Rows | 2 | |
| Mounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm) | Pitch | 0.100" (2.54mm) | |
| TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm) | Features | Card Extender | |
| Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm) | Mounting Type | Board Edge, Straddle Mount | |
| Contact FinishGoldContact Finish Thickness30µin (0.76µm) | Termination | Solder Eyelet(s) | |
| Contact Finish Thickness 30µin (0.76µm) | Contact Material | Beryllium Copper | |
| | Contact Finish | Gold | |
| Contact Type Eull Pollogy | Contact Finish Thickness | 30µin (0.76µm) | |
| Contact Type Full Benows | Contact Type | Full Bellows | |
| Color Blue | Color | Blue | |
| Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia | Flange Feature | Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia | |
| Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$ | Operating Temperature | -65°C ~ 125°C | |
| Report errors? | | Report errors? | |

HCC05DREH-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HCC05DREH-S13 Payment Methods



HCC05DREH-S13 Shipping Methods



If you have any question about HCC05DREH-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com