

HCC05DRTS-S13

HCC05DRTS-S13 Information

Heisener.com	 HCC05DRTS-S13 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 10POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HCC05DRTS-S13 Specifications

Manufacturer Part Number HCC05DRTS-S13 Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Package - Series - Gender Type Non Specified - Dual Edge Mumber of Positions/Bay/Row 5 Number of Positions/Bay/Row 5 Number of Positions 0.062° (1.57mm) Yether Series 2 Number of Rows 2 Pitch 0.100° (2.54mm) Number of Rows 2 Yether Series Solder Contact Material Solder Contact Material Solder Contact Finish Thickness Gold Contact Finish Thickness Soldin (0.76µm) Contact Type Guld Bullows Contact Type Bull Bullows Color Bull Bullows Color Side Mount Opening, Unthreaded, 0.125° (3.18mm) Dia Color Side Mount Opening, Unthreaded, 0.125° (3.18mm) Dia		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Otard Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Number of Rows2PitchSolder Edge, Straddle MountNouting TypeSolderContact MaterialSolderContact Finish Thickness0.001° (3.54mm)Contact Finish ThicknessSolderContact TypeGoldContact TypeSolderContact Finish ThicknessSoliderContact TypeFull BellowsCotact TypeSulp Coperating (3.18mm) DiaColorSide Sulp Coperating (3.18mm) DiaColorSolerColorSoler Coperating (3.18mm) DiaColorSoler Coperating (3.18mm) DiaColorSoler Coperating (3.18mm) DiaColorSoler Coperating (3.18mm) DiaColorSoler Coperating (3.18mm) DiaCoperating TemperatureSide Nout Opening, Unthreaded, 0.125° (3.18mm) Dia	Manufacturer Part Number	HCC05DRTS-S13
ActiveCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaPinage FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFaquresSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature50°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSipin (0.76µm)Contact TypeBueColorBueFalage FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaForating TemperatureSide Yan 20°C	Package	-
GenderFemaleNumber of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row5Number of Positions10Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 10 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Gold Contact Finish Thickness Gold Contact Type Full Bellows Color Bue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	5
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	10
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish ThicknessSoljun (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFul BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

HCC05DRTS-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HCC05DRTS-S13 Payment Methods





If you have any question about HCC05DRTS-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com