

HCC10DETN

uest a Quote

HCC10DETN Information

| Part Number | HCC10DETN |
|------------------------|---|
| Manufacturer | Sullins Connector Solutions |
| Category | Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors |
| Description Package | CONN EDGE DUAL FMALE 20POS 0.100 |
| | - |
| | For the pricing/inventory/lead time, please contact |
| | us Website: https://www.heisener.com E-mail: salesdept@heisener.com |
| | Manufacturer Category Description |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HCC10DETN Specifications

| ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeGoldContact TypeCantileverContact TypeContact Solut | | |
|---|-----------------------------|---|
| CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions/Bay/Row0.062" (1.57mm)Number of Positions2Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Nounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-Soler< | Manufacturer Part Number | HCC10DETN |
| Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30/uin (0.76µm)Contact Finish Thickness30/uin (0.76µm)Contact TypeCantileverContact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C | Manufacturer | Sullins Connector Solutions |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverFlange Feature-Solger-Flange Feature-Operating Temperature-55°C ~ 125°C | Category | Connectors, Interconnects |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions/Bay/Row20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C | | Card Edge Connectors - Edgeboard Connectors |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact Type-Features-SolderSolderContact Finish ThicknessGoldContact Type-Feature-Color-Flange Feature-Operating Temperature65°C ~ 12°C | Package | - |
| GenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.602° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting Type0.100° (2.54mm)Contact FinishSolderContact FinishGoldContact Finish ThicknessGoldContact TypeSini (0.76µm)Contact Finish ThicknessSini (0.76µm)ColorSini (0.76µm)Finage Feature-Operating Temperature60° < | Series | - |
| Number of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-Yongh HoleSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Forger Feature-Forger Feature-Color-Flange Feature-Cortact Type-Contact Funder-Flange Teature-Color-Contact Funder-Flange Feature-Contact Spectrum-Contact Spectrum-Color-Color-Flange Feature-Color-Color-Color-Color-Color-Color-Flange Feature-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color- <tr< td=""><td>Card Type</td><td>Non Specified - Dual Edge</td></tr<> | Card Type | Non Specified - Dual Edge |
| Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature-Operating Temperature-Solor Canter Schler-Contact Schler-Color-< | Gender | Female |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeCantileverColor-Flange Feature-Operating Temperature65°C ~ 125°C | Number of Positions/Bay/Row | 10 |
| Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C | Number of Positions | 20 |
| Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact Type-Color-Flange Feature-Operating Temperature65°C ~ 125°C | Card Thickness | 0.062" (1.57mm) |
| Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverFlange Feature-Operating Temperature65°C ~ 125°C | Number of Rows | 2 |
| Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-55°C ~ 125°C | Pitch | 0.100" (2.54mm) |
| TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C | Features | - |
| Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C | Mounting Type | Through Hole |
| Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C | Termination | Solder |
| Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C | Contact Material | Beryllium Copper |
| Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C | Contact Finish | Gold |
| Color-Flange Feature-Operating Temperature-65°C ~ 125°C | Contact Finish Thickness | 30µin (0.76µm) |
| Flange Feature-Operating Temperature-65°C ~ 125°C | Contact Type | Cantilever |
| Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$ | Color | - |
| | Flange Feature | - |
| Report errors? | Operating Temperature | $-65^{\circ}C \sim 125^{\circ}C$ |
| | | Report errors? |

HCC10DETN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HCC10DETN Payment Methods



HCC10DETN Shipping Methods



If you have any question about HCC10DETN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com