

HCC17DRYH

est a Quote

HCC17DRYH Information

Heisener.com	Part Number	HCC17DRYH	
	Manufacturer	Sullins Connector Solutions	Γ
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 34POS 0.100	
	Package	-	P F
		For the pricing/inventory/lead time, please contact	Ľ
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	1

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HCC17DRYH Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, Edgeboard ConnectorsPackage-Package-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions/Bay/Row062° (1.57mm)Number of Rows0.002° (1.57mm)Number of Rows0.002° (1.57mm)Features0.100° (2.54mm)Features0.100° (2.54mm)Found TypeSolderContact MaterialSolderContact FinishGoldContact FinishGoldContact Finish ThicknessJini Origen MaterialContact TypeSolino MaterialContact TypeSoli				
CatagoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions/Bay/Row062° (1.57mm)Number of Rows0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeMong HoleContact MaterialSolderContact FinishGoldContact Finish Thickness0.0in (0.76µm)Contact TypeHul BellowsContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Colar TypeSupin (0.75µm)Colar TypeSupin (0.125° (0.18µm)Contart TypeSupin (0.125° C	Manufacturer Part Number	HCC17DRYH		
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 17 Number of Positions 34 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Mounting Type - Mounting Type Through Hole Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions		
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Mounting Type-Mounting TypeSolderContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects		
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions/Bay/Row34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange Feature-5°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors		
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessSolin (0.76µm)Contact TypeFull BellowsColorBueColorBueFage FeatureConduct Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-6%°C ~ 125°C	Package	-		
GenderFemaleNumber of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange Feature-Operating Temperature-Operating Temperature-	Series	-		
Number of Positions/Bay/Row17Number of Positions34Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Features-Mounting TypeThrough HoleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFage FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge		
Number of Positions 34 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Bue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female		
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	17		
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	34		
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)		
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2		
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)		
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-		
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole		
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder		
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper		
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold		
Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)		
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows		
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue		
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia		
Report errors?	Operating Temperature	-65°C ~ 125°C		
			Report errors?	

HCC17DRYH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HCC17DRYH Payment Methods



HCC17DRYH Shipping Methods



If you have any question about HCC17DRYH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com