

## HCC60HETH

est a Quote

#### **HCC60HETH Information**

Heisener.com	Part Number	HCC60HETH	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	7
	Description	CONN EDGE DUAL FMALE 60POS 0.100	2
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **HCC60HETH Specifications**

Manufacturer Part Number     HCC60HETH       Manufacturer     Sullins Connector Solutions       Category     Connectors, Interconnects       Cated Edge Connectors - Edgeboard Connectors     Cated Edge Connectors - Edgeboard Connectors       Package     -       Stries     -       Gard Type     Non Specified Dual Edge       Gender     Female       Number of Positions/Bay/Row     -       Number of Positions/Bay/Row     60       Number of Positions     0.062°(1.57mm)       Number of Rows     1       Pitch     0.100°(2.54mm)       Number of Rows     -       Pitch     Solder       Contact Material     Solder       Contact Material     Solder       Contact Material     Solder       Contact Finish Thickness     Gold       Contact Finish Thickness     Solymon Contage       Contact Type     Cantilever       Contact Type     Solution Copure       Contact Finish Thickness     Solymon Contage       Contact Type     Contal Copure       Contact Type     Contact Copure <			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Order Thickness060° (1.57mm)Number of Rows1Number of Rows0.100° (2.54mm)Features-Mounting Type0.100° (2.54mm)Contact MaterialSolderContact SinishGoldContact FinishGoldContact FinishGoldContact Finish ThicknessJini (0.76µm)Contact TypeCantileverContact TypeCantileverContact Finish ThicknessSiderContact Finish ThicknessSidi (0.76µm)Contact Finish ThicknessGoldContact Finish ThicknessSidi (0.76µm)Contact TypeCantileverContact Finish ThicknessSidi (0.76µm)Contact TypeSidi (0.76µm)Contact TypeCantileverContact TypeSidi (0.76µm)Contact TypeSidi (0.750°m)Contact Type	Manufacturer Part Number	НСС60НЕТН	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Card Thickness6062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting Type-Contact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact Finish Thickness3ujni (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverFaga FeatureComot Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Card Thickness60Card Thickness0.662" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeFolderContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeGoldContact Finish ThicknessSipin (0.76µm)Contact Finish ThicknessGoldContact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenting Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness60lContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverContact Type-Color-Fange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row-Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting Type0.100" (2.54mm)TerminationSolderContact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row-Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows1Number of Rows0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialGoldContact Finish ThicknessGoldContact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions     60       Card Thickness     0.062" (1.57mm)       Number of Rows     1       Number of Rows     0.100" (2.54mm)       Features     -       Mounting Type     Ondon '0.62" (1.67mm)       Termination     -       Contact Material     Solder       Contact Finish     Gold       Contact Finish Thickness     Oup (0.76µm)       Contact Type     Cantilever       Color     -       Flange Feature     Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia       Operating Temperature     -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeSupin (0.76µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	-	
Number of Rows1Number of Rows0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	60	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeJuin (0.76µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish ThicknessJupin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-65°C ~ 125°C	Number of Rows	1	
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Beryllium Copper	
Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Cantilever	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	-	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

#### **HCC60HETH Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE UARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **HCC60HETH Payment Methods**



### **HCC60HETH Shipping Methods**



If you have any question about HCC60HETH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com