



HDM14JT82R0 Information



For Reference Only

Part Number HDM14JT82R0

Manufacturer Stackpole Electronics Inc.

Category Resistors

Through Hole Resistors

Description RES 82 OHM 1/4W 5% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HDM14JT82R0 Specifications

Manufacturer Part NumberHDM14JT82R0ManufacturerStackpole Electronics Inc.CategoryResistorsPackageAxialSeriesHDMResistance82 OhmsTolerance±5%Power (Watts)0.25W, 1/4WCompositionCarbon FilmFeaturesMoisture ResistantTemperature Coefficient-500/ +350ppm/°COperating Temperature-55°C ~ 155°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.071" Dia x 0.126" L (1.80mm x 3.20mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	•	
Category Resistors Package Axial Series HDM Resistance 82 Ohms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Carbon Film Features Moisture Resistant Temperature Coefficient -500/+350ppm/°C Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Manufacturer Part Number	HDM14JT82R0
Through Hole Resistors Package Axial Series HDM Resistance 82 Ohms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Carbon Film Features Moisture Resistant Temperature Coefficient -500/+350ppm/°C Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension Un71" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) Number of Terminations 2 Failure Rate - Sian Ommander Through Hole Resistors Axial 1.	Manufacturer	Stackpole Electronics Inc.
PackageAxialSeriesHDMResistance82 OhmsTolerance±5%Power (Watts)0.25W, 1/4WCompositionCarbon FilmFeaturesMoisture ResistantTemperature Coefficient-500/ +350ppm/°COperating Temperature-55°C ~ 155°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.071" Dia x 0.126" L (1.80mm x 3.20mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Category	Resistors
SeriesHDMResistance82 OhmsTolerance±5%Power (Watts)0.25W, 1/4WCompositionCarbon FilmFeaturesMoisture ResistantTemperature Coefficient-500/+350ppm/°COperating Temperature-55°C ~ 155°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.071" Dia x 0.126" L (1.80mm x 3.20mm)Height - Seated (Max)-Number of Terminations2Failure Rate-		Through Hole Resistors
Resistance 82 Ohms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Carbon Film Features Moisture Resistant Temperature Coefficient -500/+350ppm/°C Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Package	Axial
Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Carbon Film Features Moisture Resistant Temperature Coefficient -500/ +350ppm/°C Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Series	HDM
Power (Watts) Composition Carbon Film Features Moisture Resistant Temperature Coefficient Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Size / Dimension Onor1" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Resistance	82 Ohms
Composition Carbon Film Features Moisture Resistant Temperature Coefficient -500/ +350ppm/°C Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Tolerance	±5%
Features Moisture Resistant Temperature Coefficient -500/ +350ppm/°C Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Power (Watts)	0.25W, 1/4W
Temperature Coefficient -500/ +350ppm/°C Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Composition	Carbon Film
Operating Temperature -55°C ~ 155°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) Number of Terminations 2 Failure Rate - - - - - - - - - - - - -	Features	Moisture Resistant
Package / Case Axial Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Temperature Coefficient	-500/ +350ppm/°C
Supplier Device Package Axial Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.071" Dia x 0.126" L (1.80mm x 3.20mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Package / Case	Axial
Height - Seated (Max) Number of Terminations Failure Rate -	Supplier Device Package	Axial
Number of Terminations 2 Failure Rate -	Size / Dimension	0.071" Dia x 0.126" L (1.80mm x 3.20mm)
Failure Rate -	Height - Seated (Max)	-
	Number of Terminations	2
	Failure Rate	-
Report errors?		Report errors?

HDM14JT82R0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HDM14JT82R0 Payment Methods

































If you have any question about HDM14JT82R0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com