



Heisener.com

For Reference Only

HDWM-15-54-G-D-200 Information

Part Number HDWM-15-54-G-D-200

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

Description .050" BOARD SPACERS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HDWM-15-54-G-D-200 Specifications

Manufacturer Part Number HDWM-15-54-G-D-200 Manufacturer Samtec Inc. Category Connectors, Interconnects Package - Series Flex Stack, HDWM Number of Positions 30 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm) Color Black		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package - Series Flex Stack, HDWM Number of Positions 30 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10µin (0.25µm)	Manufacturer Part Number	HDWM-15-54-G-D-200
Package-SeriesFlex Stack, HDWMNumber of Positions30Pitch0.050" (1.27mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.555" (14.10mm)Length - Post (Mating)0.235" (5.97mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Manufacturer	Samtec Inc.
Package - Series Flex Stack, HDWM Number of Positions 30 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Category	Connectors, Interconnects
Series Flex Stack, HDWM Number of Positions 30 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions 30 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Package	-
Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Series	Flex Stack, HDWM
Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Number of Positions	30
Row Spacing 0.100" (2.54mm) Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Pitch	0.050" (1.27mm)
Length - Overall 0.555" (14.10mm) Length - Post (Mating) 0.235" (5.97mm) Length - Stack Height 0.200" (5.08mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Number of Rows	2
Length - Post (Mating)0.235" (5.97mm)Length - Stack Height0.200" (5.08mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.200" (5.08mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Overall	0.555" (14.10mm)
Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Post (Mating)	0.235" (5.97mm)
Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)GoldContact Finish Thickness - Post (Mating)10μin (0.25μm)	Length - Stack Height	0.200" (5.08mm)
Termination Solder Contact Finish - Post (Mating) Gold Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Length - Tail	0.120" (3.05mm)
Contact Finish - Post (Mating) Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Mounting Type	Through Hole
Contact Finish Thickness - Post (Mating) 10μin (0.25μm)	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Color Black	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
	Color	Black
Report errors?		Report errors?

HDWM-15-54-G-D-200 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HDWM-15-54-G-D-200 Payment Methods



















HDWM-15-54-G-D-200 Shipping Methods













If you have any question about HDWM-15-54-G-D-200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com