



HE1AN-P-DC48V Information



For Reference Only

Part Number HE1AN-P-DC48V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HE1AN-P-DC48V Specifications

Manufacturer Part NumberHEIAN-P-DC48VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesHERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time30msRelease Time10msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesHERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time30msRelease Time10msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	HE1AN-P-DC48V
Package - Series HE Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Manufacturer	Panasonic Electric Works
Package-SeriesHERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time30msRelease Time10msFeatures-Mounting TypeThrough Hole	Category	Relays
Series HE Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 40mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Series	HE
Coil Current 40mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Coil Current	40mA
Contact Rating (Current) Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Coil Voltage	48VDC
Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Switching Voltage	277VAC, 30VDC - Max
Operate Time 30ms Release Time 10ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	33.6 VDC
Release Time 10ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	4.8 VDC
Features - Through Hole	Operate Time	30ms
Mounting Type Through Hole	Release Time	10ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

HE1AN-P-DC48V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HE1AN-P-DC48V Payment Methods



















HE1AN-P-DC48V Shipping Methods













If you have any question about HE1AN-P-DC48V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com