



HE1AN-Q-DC12V Information



For Reference Only

Part Number HE1AN-Q-DC12V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HE1AN-Q-DC12V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package Series HE Relay Type General Purpose Coil Type Non Latching Coil Current 160mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features Mounting Type Chassis Mount Termination Style Panasonic Electric Works Relays Panasonic Electric Works Relays Pomore Selectric Works Aslays Power Relays, Over 2 Amps Power Relays Power Power Power Power Relays Power Relays		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesHERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current160mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time30msRelease Time10msFeatures-Mounting TypeChassis Mount	Manufacturer Part Number	HE1AN-Q-DC12V
Package - Series HE Relay Type General Purpose Coil Type Non Latching Coil Current 160mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Manufacturer	Panasonic Electric Works
Package - Series HE Relay Type General Purpose Coil Type Non Latching Coil Current 160mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Category	Relays
SeriesHERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current160mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time30msRelease Time10msFeatures-Mounting TypeChassis Mount		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 160mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Package	-
Coil TypeNon LatchingCoil Current160mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time30msRelease Time10msFeatures-Mounting TypeChassis Mount	Series	HE
Coil Current 160mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features Mounting Type Chassis Mount	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features Mounting Type Chassis Mount	Coil Current	160mA
Contact Rating (Current) Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Coil Voltage	12VDC
Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 30ms Release Time 10ms Features	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Switching Voltage	277VAC, 30VDC - Max
Operate Time 30ms Release Time 10ms Features - Mounting Type Chassis Mount	Turn On Voltage (Max)	8.4 VDC
Release Time 10ms Features - Mounting Type Chassis Mount	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Chassis Mount	Operate Time	30ms
Mounting Type Chassis Mount	Release Time	10ms
	Features	-
Termination Style Ouick Connect - 0.250" (6.3mm)	Mounting Type	Chassis Mount
Quien Commet (1250 (0151mm))	Termination Style	Quick Connect - 0.250" (6.3mm)
Report errors?		Report errors?

HE1AN-Q-DC12V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HE1AN-Q-DC12V Payment Methods



















HE1AN-Q-DC12V Shipping Methods













If you have any question about HE1AN-Q-DC12V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com