

HEG.0K.302.CLVPV

HEG.0K.302.CLVPV Information

Heisener.com	Part Number Manufacturer Category Description Package	HEG.0K.302.CLVPV LEMO Connectors, Interconnects Circular Connectors RCPT PNL MNT 2SKT R/A PCB - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HEG.0K.302.CLVPV Specifications

ManufacturerLEMOCategoryConnectors, InterconnectsCircular ConnectorsPackage-Series0KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AnglePastening TypeOlderPastening TypePush-Pull, Detent LockOrientationGIngress ProtectionPh6/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Package-Series0KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGShell Material, FinishBrass, Chrome PlatedShell Material, FinishGoldFeaturesShielded, VacuuntightFotage - Rated-Current Rating6A	Manufacturer Part Number	HEG.0K.302.CLVPV
Circular ConnectorsPackage-SeriesOKConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionH66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuumtightVoltage - Rated-Current Rating6A	Manufacturer	LEMO
Package-Series0KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionHol6/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldVoltage - Rated-Current Rating6A	Category	Connectors, Interconnects
SeriesOKConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A	Package	-
Number of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuumtightVoltage - Rated-Current Rating6A	Series	0K
Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuumtightVoltage - Rated-Current Rating6A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuumtightVoltage - Rated-Current Rating6A	Number of Positions	2
Mounting TypePanel Mount, Flange; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-GatGatKurent RatingGold	Shell Size - Insert	302
TerminationSolderFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A	Shell Size, MIL	-
Fastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A	Mounting Type	Panel Mount, Flange; Through Hole, Right Angle
OrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A	Termination	Solder
Ingress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A	Fastening Type	Push-Pull, Detent Lock
Shell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A	Orientation	G
Contact FinishGoldFeaturesShielded, VacuuntightVoltage - Rated-Current Rating6A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
FeaturesShielded, VacuumtightVoltage - Rated-Current Rating6A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 6A	Contact Finish	Gold
Current Rating 6A	Features	Shielded, Vacuumtight
-	Voltage - Rated	-
Report errors?	Current Rating	6A
		Report errors?

HEG.0K.302.CLVPV Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

HEG.0K.302.CLVPV Payment Methods



HEG.0K.302.CLVPV Shipping Methods



If you have any question about HEG.0K.302.CLVPV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com