



HFA15TB60PBF Information



For Reference Only

Part Number HFA15TB60PBF
Manufacturer Infineon Technologies

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 600V 15A TO220AC

Package TO-220-2

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HFA15TB60PBF Specifications

Manufacturer Part NumberHFA15TB60PBFManufacturerInfineon TechnologiesCategoryDiscrete Semiconductor ProductsPackageTO-220-2SeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)15AVoltage - Forward (Vf) (Max) @ If1.7V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-220-2SeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)15AVoltage - Forward (Vf) (Max) @ If1.7V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough Hole	Manufacturer Part Number	HFA15TB60PBF
Diodes - Rectifiers - Single Package TO-220-2 Series HEXFRED? Diode Type Standard Voltage - DC Reverse (Vr) (Max) 600V Current - Average Rectified (Io) 15A Voltage - Forward (Vf) (Max) @ If 1.7V @ 15A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 60ns Current - Reverse Leakage @ Vr 10µA @ 600V Capacitance @ Vr, F Mounting Type Through Hole	Manufacturer	Infineon Technologies
Package TO-220-2 Series HEXFRED? Diode Type Standard Voltage - DC Reverse (Vr) (Max) 600V Current - Average Rectified (Io) 15A Voltage - Forward (Vf) (Max) @ If 1.7V @ 15A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 60ns Current - Reverse Leakage @ Vr 10µA @ 600V Capacitance @ Vr, F Mounting Type Through Hole	Category	Discrete Semiconductor Products
SeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)15AVoltage - Forward (Vf) (Max) @ If1.7V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough Hole		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)15AVoltage - Forward (Vf) (Max) @ If1.7V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough Hole	Package	TO-220-2
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 60ns Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Through Hole	Series	HEXFRED?
Current - Average Rectified (Io) 15A Voltage - Forward (Vf) (Max) @ If 1.7V @ 15A Speed Fast Recovery =< 500 ns, > 200 mA (Io) Reverse Recovery Time (trr) 60ns Current - Reverse Leakage @ Vr 10 μ A @ 600 V Capacitance @ Vr, F - Mounting Type Through Hole	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.7V @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)60nsCurrent - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough Hole	Voltage - DC Reverse (Vr) (Max)	600V
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Average Rectified (Io)	15A
Reverse Recovery Time (trr) 60ns Current - Reverse Leakage @ Vr 10μA @ 600V Capacitance @ Vr, F - Mounting Type Through Hole	Voltage - Forward (Vf) (Max) @ If	1.7V @ 15A
Current - Reverse Leakage @ Vr 10μA @ 600V Capacitance @ Vr, F - Mounting Type Through Hole	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F - Mounting Type Through Hole	Reverse Recovery Time (trr)	60ns
Mounting Type Through Hole	Current - Reverse Leakage @ Vr	10μA @ 600V
	Capacitance @ Vr, F	-
Package / Case TO-220-2	Mounting Type	Through Hole
	Package / Case	TO-220-2
Supplier Device Package TO-220AC	Supplier Device Package	TO-220AC
Operating Temperature - Junction $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Operating Temperature - Junction	-55°C ~ 150°C
Report errors?		Report errors?

HFA15TB60PBF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HFA15TB60PBF Payment Methods



















HFA15TB60PBF Shipping Methods













If you have any question about HFA15TB60PBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com