

HFA16TB120STRR

HFA16TB120STRR Information

www.hcrsener.com	 HFA16TB120STRR Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE GEN PURP 1.2KV 16A D2PAK TO-263-3, D2Pak (2 Leads + Tab), TO-263AB For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HFA16TB120STRR Specifications

Manufacturer Part NumberHFA 16TB 120STRRManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If3V @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr20µA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseD2PAKOperating Temperature - Junction55°C ~ 150°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABPackageHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Jo)16AVoltage - Forward (Vf) (Max) @ If3V @ 16ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr20µA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction55°C ~ 150°C	Manufacturer Part Number	HFA16TB120STRR
IndexDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Jo)16AVoltage - Forward (Vf) (Max) @ If3V @ 16ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr $20\mu A @ 1200V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If3V @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr20µA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
SeriesHEXFRED?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If $3V @ 16A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr $20\mu A @ 1200V$ Capacitance @ Vr, F.Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction $-5°C ~ 150°C$		Diodes - Rectifiers - Single
Diode Type Standard Diode Type Standard Voltage - DC Reverse (Vr) (Max) 1200V Current - Average Rectified (Io) 16A Voltage - Forward (Vf) (Max) @ If 3V @ 16A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 135ns Current - Reverse Leakage @ Vr 20µA @ 1200V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction -55°C ~ 150°C	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Notage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If $3V @ 16A$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr $20\mu A @ 1200V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction -55° C ~ 150°C	Series	HEXFRED?
Current - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If3V @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr20μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $3V @ 16A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $135ns$ Current - Reverse Leakage @ Vr $20\mu A @ 1200V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Voltage - DC Reverse (Vr) (Max)	1200V
Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) 135ns Current - Reverse Leakage @ Vr 20μA @ 1200V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK Operating Temperature - Junction -55°C ~ 150°C	Current - Average Rectified (Io)	16A
Reverse Recovery Time (trr)135nsCurrent - Reverse Leakage @ Vr20μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	3V @ 16A
Current - Reverse Leakage @ Vr20μA @ 1200VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	135ns
Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	20µA @ 1200V
Package / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device PackageD2PAKOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
	Supplier Device Package	D2PAK
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

HFA16TB120STRR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HFA16TB120STRR Payment Methods





If you have any question about HFA16TB120STRR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com