



HG2-DC48V Information

Heisener.com

Part Number HG2-DC48V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 20A 48V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HG2-DC48V Specifications

Manufacturer Part Number HG2-DC48V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series HG Relay Type General Purpose Coil Type Non Latching Coil Current 30.3mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)		
Category Relays Power Relays, Over 2 Amps Package - Series HG Relay Type General Purpose Coil Type Non Latching Coil Current 30.3mA Coil Voltage 48 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	HG2-DC48V
Package - Series HG Relay Type General Purpose Coil Type Non Latching Coil Current 30.3mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Manufacturer	Panasonic Electric Works
Package - Series HG Relay Type General Purpose Coil Type Non Latching Coil Current 30.3mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesHGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30.3mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 30.3mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current30.3mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Series	HG
Coil Current30.3mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Release Time Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Coil Current	30.3mA
Contact Rating (Current) Switching Voltage 250VAC - Nom 38.4 VDC Turn Off Voltage (Max) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style 20A 250VAC - Nom 38.4 VDC 15ms 6.8 VDC 15ms 15ms 15ms 15ms Plug In, Quick Connect - 0.250" (6.3mm)	Coil Voltage	48VDC
Switching Voltage Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style 250VAC - Nom 38.4 VDC 4.8 VDC 15ms Foatures 15ms Plug In, Quick Connect - 0.250" (6.3mm)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style 138.4 VDC 4.8 VDC 6.3 Mm	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Switching Voltage	250VAC - Nom
Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	38.4 VDC
Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	4.8 VDC
Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Release Time	15ms
Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.250" (6.3mm)
		Report errors?

HG2-DC48V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HG2-DC48V Payment Methods



















HG2-DC48V Shipping Methods













If you have any question about HG2-DC48V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com