



HG3-DC24V Information

Heisener.com

Part Number HG3-DC24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 20A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HG3-DC24V Specifications

Manufacturer Part Number HG3-DC24V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series HG Relay Type General Purpose Coil Type Non Latching Coil Current 66mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm) Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesHGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	HG3-DC24V
Package - Series HG Relay Type General Purpose Coil Type Non Latching Coil Current 66mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Manufacturer	Panasonic Electric Works
Package - General Purpose General Purpose Coil Type Non Latching Coil Current 66mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Pulg In, Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesHGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current66mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Series	HG
Coil Current Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Coil Current	66mA
Contact Rating (Current) Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style 20A 250VAC - Nom 19.2 VDC 2.4 VDC 2.5 WDC 2.5 WDC 2.5 WDC 25ms Plug In, Quick Connect - 0.250" (6.3mm)	Coil Voltage	24VDC
Switching Voltage 250VAC - Nom Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style 19.2 VDC 2.4 VDC 2.5 Mounting Type Socketable Plug In, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Switching Voltage	250VAC - Nom
Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	19.2 VDC
Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Release Time	25ms
Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.250" (6.3mm)
		Report errors?

HG3-DC24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HG3-DC24V Payment Methods



















HG3-DC24V Shipping Methods













If you have any question about HG3-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com