

HI05-1A66 Information

Wines Ines

Part Number HI05-1A66

Manufacturer Standex-Meder Electronics

Category Relays

Signal Relays, Up to 2 Amps

Description REED RELAY SPST-NO 5V PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HI05-1A66 Specifications

Manufacturer Part Number Manufacturer Standex-Meder Electronics Relays Signal Relays, Up to 2 Amps Package		
CategoryRelaysPackage-SeriesHIRelay TypeReedCoil TypeNon LatchingCoil Current8.3mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time0.7msRelease Time0.05msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	HI05-1A66
Package-SeriesHIRelay TypeReedCoil TypeNon LatchingCoil Current8.3mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time0.7msRelease Time0.05msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Standex-Meder Electronics
Package-SeriesHIRelay TypeReedCoil TypeNon LatchingCoil Current8.3mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time0.7msRelease Time0.05msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesHIRelay TypeReedCoil TypeNon LatchingCoil Current8.3mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time0.7msRelease Time0.05msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current8.3mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time0.7msRelease Time0.05msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current8.3mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time0.7msRelease Time0.05msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	HI
Coil Current 8.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 0.7ms Release Time 0.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 0.75 VDC Release Time 0.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 0.7ms Release Time 0.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 0.7ms Release Time 0.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) Operate Time 0.7ms Release Time 0.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 3.5 VDC 0.75 VDC 0.7ms Fourther Control of the control of t	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time O.7ms Release Time O.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style 3.5 VDC 0.77 S 0.07 ms Features PC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.75 VDC Operate Time 0.7ms Release Time 0.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.7msRelease Time0.05msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time 0.05ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.75 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.7ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.05ms
Termination Style PC Pin	Features	Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
The state of the s		Report errors?

HI05-1A66 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HI05-1A66 Payment Methods


































If you have any question about HI05-1A66, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com