

HIF3H-60DA-2.54DSA(71) Information

| www.helsene.com | HIF3H-60DA-2.54DSA(71) Hirose Electric Co Ltd Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN HOUSING 60POS 2.54MM DUAL | |
|--------------------|---|-----------------|
| For Reference Only | For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HIF3H-60DA-2.54DSA(71) Specifications

| Manufacturer Part Number | HIF3H-60DA-2.54DSA(71) |
|-----------------------------------|---|
| Manufacturer | Hirose Electric Co Ltd |
| Category | Connectors, Interconnects |
| | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Package | - |
| Series | HIF3H |
| Connector Type | Receptacle |
| Contact Type | Female Socket |
| Style | Board to Board |
| Number of Positions | 60 |
| Number of Positions Loaded | All |
| Pitch - Mating | 0.100" (2.54mm) |
| Number of Rows | 2 |
| Row Spacing - Mating | 0.100" (2.54mm) |
| Mounting Type | Through Hole |
| Termination | Solder |
| Fastening Type | - |
| Contact Finish - Mating | Gold |
| Contact Finish Thickness - Mating | 8µin (0.20µm) |
| Insulation Color | Black |
| Insulation Height | 0.374" (9.50mm) |
| Contact Length - Post | 0.118" (3.00mm) |
| Operating Temperature | -55°C ~ 85°C |
| Material Flammability Rating | UL94 V-0 |

| Contact Finish - Post | Tin |
|------------------------|----------------|
| Mated Stacking Heights | - |
| Ingress Protection | - |
| Features | - |
| | Report errors? |



If you have any question about HIF3H-60DA-2.54DSA(71), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com